



Bridgelux Vero® SE Series LED Array: Product Selection Guide PSG-120 Rev. A

Refer to relevant product data sheets for specific information on application and performance.
 Product Data sheets available at Bridgelux.com or from Bridgelux Sales Representatives.
 The tables below include the base BXRC part number which defines color (CCT), color rendering (CRI) and flux characteristics.

Product Nomenclature – BXRC (Vero SE) Series Part Numbers

Product Number: **B X R C – A B C D E F G - H - I J - SE**

B X R C . designates product family

A B . designates nominal CCT color

- 27 - 2700 K
- 30 - 3000 K
- 35 - 3500 K
- 40 - 4000 K
- 50 - 5000 K
- 56 - 5600 K
- 65 - 6500 K

C - Color Rendering (CRI)

- C - CRI > 70
- E - CRI > 80
- G - CRI > 90
- H - CRI > 97
- A - Class A

D E F G . designates nominal flux. (Example: 1000 for 1000 lumen product)

H - Array Configuration

I - Gen. 7

J . designates color binning

- 2 - 3SDCM (2-step) available on Warm and Neutral White
- 3 - 3SDCM (3-step) available on Warm and Neutral White
- 4 - 4SDCM (4-step) available on Cool White

SE . designates Special Edition

Vero SE (BXRC) Form Factors



Vero 10 SE



Vero 13 SE



Vero 18 SE



Vero 29 SE

Form Factor	MOQ	Tray Count	LES Diameter	Outer Diameter	Total Z-Height
Vero SE 10	100	100 units	10 mm	31 mm	3.5 mm
Vero SE 13	100	100 units	13 mm	36 mm	3.5 mm
Vero SE 18	100	100 units	18 mm	36 mm	3.5 mm
Vero SE 29	50	50 units	29 mm	49 mm	3.5 mm

Notes:

1.) Thermal Resistance based on 3000K 80 CRI component.



Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Vero SE 10	BXRC-27E1000-B-7x-SE	2700K	80	135	-	699	615	33.3	4.5	155	-	628	553	32.3	4.4	144	DS120
				180	-	916	806	33.8	6.1	151	-	822	723	32.8	5.9	139	
				270	1x	1311	1154	35.0	9.5	139	0.49	1180	1039	34.0	9.2	128	
				405	1.5x	1923	1693	36.4	14.7	130	-	1711	1506	35.4	14.4	119	
				540	2x	2464	2169	37.8	20.4	121	0.57	2181	1920	36.8	19.9	110	
Vero SE 10	BXRC-27E1000-C-7x-SE	2700K	80	180	-	929	817	33.3	6.0	155	-	829	729	32.3	5.8	142	DS120
				240	-	1217	1071	33.8	8.1	150	-	1081	951	32.8	7.9	137	
				360	1x	1747	1537	35.0	12.6	139	0.37	1572	1383	34.0	12.3	128	
				540	1.5x	2544	2238	36.4	19.7	129	-	2210	1944	35.4	19.1	115	
				720	2x	3250	2859	37.7	27.1	120	0.43	2782	2447	36.7	26.4	105	
Vero SE 10	BXRC-27E1000-D-7x-SE	2700K	80	175	-	680	599	24.9	4.4	156	-	619	544	24.2	4.2	146	DS120
				233	-	892	785	25.4	5.9	151	-	802	706	24.7	5.8	139	
				350	1x	1274	1121	26.0	9.1	140	0.49	1147	1009	25.3	8.9	130	
				525	1.5x	1875	1650	27.4	14.4	130	-	1617	1423	26.7	14.0	115	
				700	2x	2403	2114	28.4	19.9	121	0.57	2023	1780	27.7	19.4	104	
Vero SE 10	BXRC-27G1000-B-7x-SE	2700K	90	135	-	582	512	33.3	4.5	129	-	523	460	32.3	4.4	120	DS120
				180	-	763	671	33.8	6.1	125	-	684	602	32.8	5.9	116	
				270	1x	1092	961	35.0	9.5	116	0.49	983	865	34.0	9.2	107	
				405	1.5x	1602	1410	36.4	14.7	109	-	1425	1254	35.4	14.4	99	
				540	2x	2052	1806	37.8	20.4	101	0.57	1817	1599	36.8	19.9	91	
Vero SE 10	BXRC-27G1000-C-7x-SE	2700K	90	180	-	774	681	33.3	6.0	129	-	691	608	32.3	5.8	119	DS120
				240	-	1014	892	33.8	8.1	125	-	901	793	32.8	7.9	114	
				360	1x	1456	1281	35.0	12.6	116	0.37	1310	1153	34.0	12.3	107	
				540	1.5x	2120	1865	36.4	19.7	108	-	1842	1620	35.4	19.1	96	
				720	2x	2708	2383	37.7	27.1	100	0.43	2318	2040	36.7	26.4	88	
Vero SE 10	BXRC-27G1000-D-7x-SE	2700K	90	175	-	566	499	24.9	4.4	130	-	515	453	24.2	4.2	122	DS120
				233	-	743	654	25.4	5.9	126	-	668	588	24.7	5.8	116	
				350	1x	1061	934	26.0	9.1	117	0.49	955	841	25.3	8.9	108	
				525	1.5x	1562	1375	27.4	14.4	109	-	1347	1186	26.7	14.0	96	
				700	2x	2001	1761	28.4	19.9	101	0.57	1685	1483	27.7	19.4	87	
Vero SE 10	BXRC-30E1000-B-7x-SE	3000K	80	135	-	734	640	33.3	4.5	163	-	660	575	32.3	4.4	151	DS120
				180	-	963	839	33.8	6.1	158	-	864	753	32.8	5.9	146	
				270	1x	1378	1201	35.0	9.5	146	0.49	1240	1081	34.0	9.2	135	
				405	1.5x	2022	1762	36.4	14.7	137	-	1798	1567	35.4	14.4	125	
				540	2x	2590	2257	37.8	20.4	127	0.57	2292	1998	36.8	19.9	115	
Vero SE 10	BXRC-30E1000-C-7x-SE	3000K	80	180	-	977	851	33.3	6.0	163	-	872	760	32.3	5.8	150	DS120
				240	-	1280	1115	33.8	8.1	158	-	1137	991	32.8	7.9	144	
				360	1x	1837	1601	35.0	12.6	146	0.37	1653	1441	34.0	12.3	135	
				540	1.5x	2675	2331	36.4	19.7	136	-	2324	2025	35.4	19.1	121	
				720	2x	3417	2978	37.7	27.1	126	0.43	2925	2549	36.7	26.4	111	
Vero SE 10	BXRC-30E1000-D-7x-SE	3000K	80	175	-	709	623	24.9	4.4	163	-	644	567	24.2	4.2	152	DS120
				233	-	930	817	25.4	5.9	157	-	836	735	24.7	5.8	145	
				350	1x	1327	1167	26.0	9.1	146	0.49	1194	1050	25.3	8.9	135	
				525	1.5x	1953	1718	27.4	14.4	136	-	1685	1482	26.7	14.0	120	
				700	2x	2502	2201	28.4	19.9	126	0.57	2107	1853	27.7	19.4	109	
Vero SE 10	BXRC-30G1000-B-7x-SE	3000K	90	135	-	604	531	33.3	4.5	134	-	543	477	32.3	4.4	124	DS120
				180	-	792	697	33.8	6.1	130	-	710	625	32.8	5.9	120	
				270	1x	1133	997	35.0	9.5	120	0.49	1020	897	34.0	9.2	111	
				405	1.5x	1662	1463	36.4	14.7	113	-	1479	1301	35.4	14.4	103	
				540	2x	2129	1874	37.8	20.4	104	0.57	1885	1659	36.8	19.9	95	
Vero SE 10	BXRC-30G1000-C-7x-SE	3000K	90	180	-	803	707	33.3	6.0	134	-	716	631	32.3	5.8	123	DS120
				240	-	1052	926	33.8	8.1	130	-	934	822	32.8	7.9	119	
				360	1x	1510	1329	35.0	12.6	120	0.37	1359	1196	34.0	12.3	111	
				540	1.5x	2199	1935	36.4	19.7	112	-	1910	1681	35.4	19.1	100	
				720	2x	2809	2472	37.7	27.1	103	0.43	2404	2116	36.7	26.4	91	
Vero SE 10	BXRC-30G1000-D-7x-SE	3000K	90	175	-	588	517	24.9	4.4	135	-	535	470	24.2	4.2	126	DS120
				233	-	771	679	25.4	5.9	130	-	693	610	24.7	5.8	121	
				350	1x	1101	969	26.0	9.1	121	0.49	991	872	25.3	8.9	112	
				525	1.5x	1621	1426	27.4	14.4	113	-	1398	1230	26.7	14.0	100	
				700	2x	2076	1827	28.4	19.9	104	0.57	1748	1539	27.7	19.4	90	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Vero SE 10	BXRC-35E1000-B-7x-SE	3500K	80	135	-	749	659	33.3	4.5	167	-	673	592	32.3	4.4	154	DS120
				180	-	982	864	33.8	6.1	161	-	881	775	32.8	5.9	149	
				270	1x	1406	1237	35.0	9.5	149	0.49	1265	1113	34.0	9.2	138	
				405	1.5x	2063	1815	36.4	14.7	140	-	1835	1614	35.4	14.4	128	
				540	2x	2643	2325	37.8	20.4	129	0.57	2339	2058	36.8	19.9	118	
Vero SE 10	BXRC-35E1000-C-7x-SE	3500K	80	180	-	996	877	33.3	6.0	166	-	889	782	32.3	5.8	153	DS120
				240	-	1305	1149	33.8	8.1	161	-	1160	1020	32.8	7.9	147	
				360	1x	1874	1649	35.0	12.6	149	0.37	1687	1484	34.0	12.3	138	
				540	1.5x	2729	2401	36.4	19.7	139	-	2371	2086	35.4	19.1	124	
				720	2x	3486	3067	37.7	27.1	128	0.43	2984	2626	36.7	26.4	113	
Vero SE 10	BXRC-35E1000-D-7x-SE	3500K	80	175	-	730	642	24.9	4.4	167	-	664	584	24.2	4.2	157	DS120
				233	-	958	842	25.4	5.9	162	-	861	757	24.7	5.8	150	
				350	1x	1367	1202	26.0	9.1	150	0.49	1230	1082	25.3	8.9	139	
				525	1.5x	2012	1769	27.4	14.4	140	-	1735	1526	26.7	14.0	124	
				700	2x	2578	2267	28.4	19.9	130	0.57	2171	1909	27.7	19.4	112	
Vero SE 10	BXRC-35G1000-B-7x-SE	3500K	90	135	-	626	550	33.3	4.5	139	-	562	495	32.3	4.4	129	DS120
				180	-	820	722	33.8	6.1	135	-	736	647	32.8	5.9	124	
				270	1x	1174	1033	35.0	9.5	124	0.49	1057	930	34.0	9.2	115	
				405	1.5x	1722	1515	36.4	14.7	117	-	1532	1348	35.4	14.4	107	
				540	2x	2207	1942	37.8	20.4	108	0.57	1953	1718	36.8	19.9	98	
Vero SE 10	BXRC-35G1000-C-7x-SE	3500K	90	180	-	832	732	33.3	6.0	139	-	742	653	32.3	5.8	128	DS120
				240	-	1090	959	33.8	8.1	134	-	968	852	32.8	7.9	123	
				360	1x	1565	1377	35.0	12.6	124	0.37	1409	1239	34.0	12.3	115	
				540	1.5x	2279	2005	36.4	19.7	116	-	1980	1742	35.4	19.1	103	
				720	2x	2911	2561	37.7	27.1	107	0.43	2492	2192	36.7	26.4	94	
Vero SE 10	BXRC-35G1000-D-7x-SE	3500K	90	175	-	609	536	24.9	4.4	140	-	554	487	24.2	4.2	131	DS120
				233	-	799	703	25.4	5.9	135	-	719	632	24.7	5.8	125	
				350	1x	1141	1004	26.0	9.1	125	0.49	1027	904	25.3	8.9	116	
				525	1.5x	1679	1478	27.4	14.4	117	-	1448	1275	26.7	14.0	103	
				700	2x	2152	1893	28.4	19.9	108	0.57	1812	1594	27.7	19.4	93	
Vero SE 10	BXRC-40E1000-B-7x-SE	4000K	80	135	-	757	666	33.3	4.5	168	-	680	598	32.3	4.4	156	DS120
				180	-	992	873	33.8	6.1	163	-	890	783	32.8	5.9	151	
				270	1x	1420	1249	35.0	9.5	150	0.49	1278	1124	34.0	9.2	139	
				405	1.5x	2083	1832	36.4	14.7	141	-	1853	1630	35.4	14.4	129	
				540	2x	2669	2347	37.8	20.4	131	0.57	2362	2078	36.8	19.9	119	
Vero SE 10	BXRC-40E1000-C-7x-SE	4000K	80	180	-	1006	885	33.3	6.0	168	-	898	790	32.3	5.8	154	DS120
				240	-	1318	1160	33.8	8.1	162	-	1171	1030	32.8	7.9	149	
				360	1x	1892	1665	35.0	12.6	150	0.37	1703	1499	34.0	12.3	139	
				540	1.5x	2755	2424	36.4	19.7	140	-	2393	2106	35.4	19.1	125	
				720	2x	3519	3097	37.7	27.1	130	0.43	3012	2651	36.7	26.4	114	
Vero SE 10	BXRC-40E1000-D-7x-SE	4000K	80	175	-	737	648	24.9	4.4	169	-	670	589	24.2	4.2	158	DS120
				233	-	967	850	25.4	5.9	163	-	869	765	24.7	5.8	151	
				350	1x	1380	1214	26.0	9.1	152	0.49	1242	1093	25.3	8.9	140	
				525	1.5x	2031	1787	27.4	14.4	141	-	1752	1541	26.7	14.0	125	
				700	2x	2602	2289	28.4	19.9	131	0.57	2191	1928	27.7	19.4	113	
Vero SE 10	BXRC-40G1000-B-7x-SE	4000K	90	135	-	647	570	33.3	4.5	144	-	582	512	32.3	4.4	133	DS120
				180	-	849	747	33.8	6.1	140	-	761	670	32.8	5.9	129	
				270	1x	1215	1069	35.0	9.5	129	0.49	1094	962	34.0	9.2	119	
				405	1.5x	1782	1568	36.4	14.7	121	-	1586	1395	35.4	14.4	110	
				540	2x	2284	2009	37.8	20.4	112	0.57	2021	1778	36.8	19.9	102	
Vero SE 10	BXRC-40G1000-C-7x-SE	4000K	90	180	-	861	758	33.3	6.0	144	-	768	676	32.3	5.8	132	DS120
				240	-	1128	993	33.8	8.1	139	-	1002	882	32.8	7.9	127	
				360	1x	1619	1425	35.0	12.6	128	0.37	1457	1283	34.0	12.3	119	
				540	1.5x	2357	2075	36.4	19.7	120	-	2048	1803	35.4	19.1	107	
				720	2x	3011	2651	37.7	27.1	111	0.43	2578	2269	36.7	26.4	97	
Vero SE 10	BXRC-40G1000-D-7x-SE	4000K	90	175	-	631	555	24.9	4.4	145	-	573	504	24.2	4.2	135	DS120
				233	-	827	728	25.4	5.9	140	-	744	654	24.7	5.8	129	
				350	1x	1181	1039	26.0	9.1	130	0.49	1063	935	25.3	8.9	120	
				525	1.5x	1738	1529	27.4	14.4	121	-	1499	1319	26.7	14.0	107	
				700	2x	2227	1959	28.4	19.9	112	0.57	1875	1650	27.7	19.4	97	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Vero SE 10	BXRC-50C1001-B-74-SE	5000K	70	135	-	829	730	33.3	4.5	184	-	745	656	32.3	4.4	171	DS120
				180	-	1087	957	33.8	6.1	179	-	975	859	32.8	5.9	165	
				270	1x	1556	1370	35.0	9.5	165	0.49	1400	1233	34.0	9.2	152	
				405	1.5x	2283	2010	36.4	14.7	155	-	2031	1788	35.4	14.4	142	
				540	2x	2925	2575	37.8	20.4	143	0.57	2588	2279	36.8	19.9	130	
Vero SE 10	BXRC-50C1001-C-74-SE	5000K	70	180	-	1103	970	33.3	6.0	184	-	984	866	32.3	5.8	169	DS120
				240	-	1445	1271	33.8	8.1	178	-	1283	1129	32.8	7.9	163	
				360	1x	2074	1825	35.0	12.6	165	0.37	1867	1643	34.0	12.3	152	
				540	1.5x	3020	2657	36.4	19.7	154	-	2624	2309	35.4	19.1	137	
				720	2x	3858	3395	37.7	27.1	142	0.43	3302	2906	36.7	26.4	125	
Vero SE 10	BXRC-50C1001-D-74-SE	5000K	70	175	-	808	711	24.9	4.4	185	-	735	646	24.2	4.2	174	DS120
				233	-	1060	932	25.4	5.9	179	-	953	838	24.7	5.8	166	
				350	1x	1513	1331	26.0	9.1	166	0.49	1362	1198	25.3	8.9	154	
				525	1.5x	2227	1959	27.4	14.4	155	-	1921	1690	26.7	14.0	137	
				700	2x	2853	2510	28.4	19.9	144	0.57	2403	2114	27.7	19.4	124	
Vero SE 10	BXRC-50E1001-B-74-SE	5000K	80	135	-	780	686	33.3	4.5	173	-	701	616	32.3	4.4	160	DS120
				180	-	1022	899	33.8	6.1	168	-	917	807	32.8	5.9	155	
				270	1x	1463	1287	35.0	9.5	155	0.49	1317	1158	34.0	9.2	143	
				405	1.5x	2146	1888	36.4	14.7	146	-	1909	1680	35.4	14.4	133	
				540	2x	2750	2419	37.8	20.4	135	0.57	2434	2141	36.8	19.9	122	
Vero SE 10	BXRC-50E1001-C-74-SE	5000K	80	180	-	1037	912	33.3	6.0	173	-	925	814	32.3	5.8	159	DS120
				240	-	1358	1195	33.8	8.1	167	-	1207	1062	32.8	7.9	153	
				360	1x	1950	1716	35.0	12.6	155	0.37	1755	1544	34.0	12.3	143	
				540	1.5x	2839	2499	36.4	19.7	144	-	2467	2171	35.4	19.1	129	
				720	2x	3627	3192	37.7	27.1	134	0.43	3105	2732	36.7	26.4	117	
Vero SE 10	BXRC-50E1001-D-74-SE	5000K	80	175	-	759	668	24.9	4.4	174	-	690	607	24.2	4.2	163	DS120
				233	-	996	876	25.4	5.9	168	-	896	788	24.7	5.8	156	
				350	1x	1422	1251	26.0	9.1	156	0.49	1280	1126	25.3	8.9	145	
				525	1.5x	2093	1841	27.4	14.4	146	-	1805	1588	26.7	14.0	129	
				700	2x	2682	2359	28.4	19.9	135	0.57	2258	1987	27.7	19.4	116	
Vero SE 10	BXRC-50G1001-B-74-SE	5000K	90	135	-	663	583	33.3	4.5	148	-	596	524	32.3	4.4	137	DS120
				180	-	870	765	33.8	6.1	143	-	780	686	32.8	5.9	132	
				270	1x	1245	1095	35.0	9.5	132	0.49	1121	986	34.0	9.2	122	
				405	1.5x	1827	1606	36.4	14.7	124	-	1625	1429	35.4	14.4	113	
				540	2x	2340	2058	37.8	20.4	115	0.57	2071	1822	36.8	19.9	104	
Vero SE 10	BXRC-50G1001-C-74-SE	5000K	90	180	-	882	776	33.3	6.0	147	-	787	693	32.3	5.8	135	DS120
				240	-	1156	1017	33.8	8.1	142	-	1027	903	32.8	7.9	130	
				360	1x	1659	1460	35.0	12.6	132	0.37	1493	1314	34.0	12.3	122	
				540	1.5x	2416	2126	36.4	19.7	123	-	2099	1847	35.4	19.1	110	
				720	2x	3086	2716	37.7	27.1	114	0.43	2641	2325	36.7	26.4	100	
Vero SE 10	BXRC-50G1001-D-74-SE	5000K	90	175	-	646	568	24.9	4.4	148	-	587	517	24.2	4.2	139	DS120
				233	-	848	745	25.4	5.9	143	-	762	670	24.7	5.8	132	
				350	1x	1210	1064	26.0	9.1	133	0.49	1089	958	25.3	8.9	123	
				525	1.5x	1781	1566	27.4	14.4	124	-	1536	1351	26.7	14.0	110	
				700	2x	2282	2006	28.4	19.9	115	0.57	1921	1690	27.7	19.4	99	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Vero SE 10	BXRC-57C1001-B-74-SE	5700K	70	135	-	800	704	33.3	4.5	178	-	719	633	32.3	4.4	165	DS120
				180	-	1049	924	33.8	6.1	172	-	941	828	32.8	5.9	159	
				270	1x	1502	1322	35.0	9.5	159	0.49	1352	1190	34.0	9.2	147	
				405	1.5x	2204	1939	36.4	14.7	149	-	1960	1725	35.4	14.4	137	
				540	2x	2823	2485	37.8	20.4	138	0.57	2499	2199	36.8	19.9	126	
Vero SE 10	BXRC-57C1001-C-74-SE	5700K	70	180	-	1064	936	33.3	6.0	178	-	950	835	32.3	5.8	163	DS120
				240	-	1394	1227	33.8	8.1	172	-	1239	1090	32.8	7.9	157	
				360	1x	2002	1761	35.0	12.6	159	0.37	1802	1585	34.0	12.3	147	
				540	1.5x	2915	2564	36.4	19.7	148	-	2532	2228	35.4	19.1	132	
				720	2x	3724	3276	37.7	27.1	137	0.43	3188	2804	36.7	26.4	121	
Vero SE 10	BXRC-57C1001-D-74-SE	5700K	70	175	-	779	686	24.9	4.4	179	-	708	623	24.2	4.2	167	DS120
				233	-	1022	899	25.4	5.9	173	-	919	809	24.7	5.8	160	
				350	1x	1459	1284	26.0	9.1	160	0.49	1313	1156	25.3	8.9	148	
				525	1.5x	2148	1890	27.4	14.4	149	-	1852	1630	26.7	14.0	132	
				700	2x	2751	2421	28.4	19.9	138	0.57	2317	2039	27.7	19.4	120	
Vero SE 10	BXRC-57E1001-B-74-SE	5700K	80	135	-	793	698	33.3	4.5	176	-	713	627	32.3	4.4	163	DS120
				180	-	1040	915	33.8	6.1	171	-	933	820	32.8	5.9	158	
				270	1x	1488	1309	35.0	9.5	157	0.49	1339	1178	34.0	9.2	146	
				405	1.5x	2183	1920	36.4	14.7	148	-	1942	1708	35.4	14.4	135	
				540	2x	2797	2460	37.8	20.4	137	0.57	2475	2178	36.8	19.9	124	
Vero SE 10	BXRC-57E1001-C-74-SE	5700K	80	180	-	1054	928	33.3	6.0	176	-	941	828	32.3	5.8	162	DS120
				240	-	1381	1216	33.8	8.1	170	-	1227	1080	32.8	7.9	156	
				360	1x	1983	1746	35.0	12.6	157	0.37	1785	1571	34.0	12.3	146	
				540	1.5x	2888	2542	36.4	19.7	147	-	2508	2209	35.4	19.1	131	
				720	2x	3688	3248	37.7	27.1	136	0.43	3157	2780	36.7	26.4	119	
Vero SE 10	BXRC-57E1001-D-74-SE	5700K	80	175	-	772	679	24.9	4.4	177	-	702	618	24.2	4.2	166	DS120
				233	-	1013	891	25.4	5.9	171	-	911	801	24.7	5.8	158	
				350	1x	1446	1272	26.0	9.1	159	0.49	1301	1145	25.3	8.9	147	
				525	1.5x	2128	1872	27.4	14.4	148	-	1836	1615	26.7	14.0	131	
				700	2x	2727	2399	28.4	19.9	137	0.57	2296	2020	27.7	19.4	118	
Vero SE 10	BXRC-65C1001-B-74-SE	6500K	70	135	-	815	717	33.3	4.5	181	-	732	644	32.3	4.4	168	DS120
				180	-	1068	940	33.8	6.1	176	-	958	843	32.8	5.9	162	
				270	1x	1529	1345	35.0	9.5	162	0.49	1376	1211	34.0	9.2	150	
				405	1.5x	2243	1973	36.4	14.7	152	-	1995	1755	35.4	14.4	139	
				540	2x	2874	2528	37.8	20.4	141	0.57	2543	2237	36.8	19.9	128	
Vero SE 10	BXRC-65C1001-C-74-SE	6500K	70	180	-	1084	953	33.3	6.0	181	-	967	851	32.3	5.8	166	DS120
				240	-	1420	1249	33.8	8.1	175	-	1261	1109	32.8	7.9	160	
				360	1x	2038	1793	35.0	12.6	162	0.37	1834	1614	34.0	12.3	150	
				540	1.5x	2968	2611	36.4	19.7	151	-	2578	2268	35.4	19.1	135	
				720	2x	3791	3335	37.7	27.1	140	0.43	3245	2855	36.7	26.4	123	
Vero SE 10	BXRC-65C1001-D-74-SE	6500K	70	175	-	793	698	24.9	4.4	182	-	721	635	24.2	4.2	170	DS120
				233	-	1041	916	25.4	5.9	176	-	936	823	24.7	5.8	163	
				350	1x	1486	1307	26.0	9.1	163	0.49	1337	1176	25.3	8.9	151	
				525	1.5x	2187	1924	27.4	14.4	152	-	1886	1659	26.7	14.0	135	
				700	2x	2802	2465	28.4	19.9	141	0.57	2360	2076	27.7	19.4	122	
Vero SE 10	BXRC-65E1001-B-74-SE	6500K	80	135	-	807	711	33.3	4.5	180	-	725	639	32.3	4.4	166	DS120
				180	-	1059	932	33.8	6.1	174	-	949	836	32.8	5.9	161	
				270	1x	1515	1334	35.0	9.5	160	0.49	1364	1201	34.0	9.2	148	
				405	1.5x	2223	1957	36.4	14.7	151	-	1977	1741	35.4	14.4	138	
				540	2x	2847	2507	37.8	20.4	139	0.57	2520	2219	36.8	19.9	127	
Vero SE 10	BXRC-65E1001-C-74-SE	6500K	80	180	-	1074	945	33.3	6.0	179	-	958	844	32.3	5.8	165	DS120
				240	-	1407	1238	33.8	8.1	173	-	1250	1100	32.8	7.9	159	
				360	1x	2020	1778	35.0	12.6	160	0.37	1818	1600	34.0	12.3	148	
				540	1.5x	2941	2589	36.4	19.7	150	-	2555	2249	35.4	19.1	134	
				720	2x	3757	3307	37.7	27.1	138	0.43	3216	2831	36.7	26.4	122	
Vero SE 10	BXRC-65E1001-D-74-SE	6500K	80	175	-	786	692	24.9	4.4	180	-	715	629	24.2	4.2	169	DS120
				233	-	1032	908	25.4	5.9	174	-	928	816	24.7	5.8	161	
				350	1x	1473	1296	26.0	9.1	162	0.49	1326	1166	25.3	8.9	150	
				525	1.5x	2168	1908	27.4	14.4	151	-	1870	1645	26.7	14.0	133	
				700	2x	2778	2444	28.4	19.9	140	0.57	2339	2058	27.7	19.4	121	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Vero SE 13	BXRC-27E2000-B-7x-SE	2700K	80	113	-	620	558	32.3	3.6	170	-	568	511	31.4	3.5	160	DS121
				225	-	1200	1080	33.2	7.5	161	-	1088	979	32.3	7.3	150	
				450	1x	2276	2048	35.0	15.8	145	0.28	2048	1843	34.1	15.3	133	
				675	1.5x	3289	2960	36.3	24.5	134	-	2880	2592	35.4	23.9	121	
				900	2x	4196	3775	37.5	33.8	124	0.35	3604	3243	36.6	32.9	109	
Vero SE 13	BXRC-27E2000-C-7x-SE	2700K	80	158	-	861	775	32.3	5.1	169	-	814	732	31.4	5.0	164	DS121
				315	-	1666	1500	33.2	10.5	159	-	1569	1412	32.3	10.2	154	
				630	1x	3186	2867	35.0	22.1	144	0.20	2867	2580	34.1	21.5	133	
				945	1.5x	4573	4115	36.4	34.4	133	-	4275	3847	35.5	33.6	127	
				1260	2x	5836	5252	37.8	47.6	123	0.24	5438	4894	36.9	46.5	117	
Vero SE 13	BXRC-27E2000-D-7x-SE	2700K	80	125	-	614	552	29.6	3.7	166	-	586	527	28.7	3.6	163	DS121
				250	-	1189	1070	30.3	7.6	157	-	1133	1020	29.4	7.4	154	
				500	1x	2318	2086	31.8	15.9	146	0.34	2086	1877	30.9	15.5	135	
				750	1.5x	3276	2948	33.2	24.9	132	-	3103	2793	32.3	24.2	128	
				1000	2x	4188	3769	34.4	34.4	122	0.41	3958	3562	33.5	33.5	118	
Vero SE 13	BXRC-27G2000-B-7x-SE	2700K	90	113	-	517	465	32.3	3.6	142	-	473	426	31.4	3.5	133	DS121
				225	-	1000	900	33.2	7.5	134	-	907	816	32.3	7.3	125	
				450	1x	1897	1707	35.0	15.8	120	0.28	1707	1536	34.1	15.3	111	
				675	1.5x	2741	2467	36.3	24.5	112	-	2401	2160	35.4	23.9	100	
				900	2x	3497	3147	37.5	33.8	104	0.35	3004	2703	36.6	32.9	91	
Vero SE 13	BXRC-27G2000-C-7x-SE	2700K	90	158	-	717	645	32.3	5.1	141	-	678	610	31.4	5.0	137	DS121
				315	-	1389	1250	33.2	10.5	133	-	1308	1177	32.3	10.2	128	
				630	1x	2655	2389	35.0	22.1	120	0.20	2390	2150	34.1	21.5	111	
				945	1.5x	3811	3429	36.4	34.4	111	-	3562	3206	35.5	33.6	106	
				1260	2x	4864	4376	37.8	47.6	102	0.24	4532	4078	36.9	46.5	97	
Vero SE 13	BXRC-27G2000-D-7x-SE	2700K	90	125	-	511	460	29.6	3.7	138	-	488	440	28.7	3.6	136	DS121
				250	-	991	892	30.3	7.6	131	-	944	850	29.4	7.4	128	
				500	1x	1932	1739	31.8	15.9	122	0.34	1739	1565	30.9	15.5	113	
				750	1.5x	2730	2457	33.2	24.9	110	-	2586	2328	32.3	24.2	107	
				1000	2x	3491	3142	34.4	34.4	101	0.41	3299	2969	33.5	33.5	98	
Vero SE 13	BXRC-30E2000-B-7x-SE	3000K	80	113	-	646	581	32.3	3.6	177	-	592	533	31.4	3.5	167	DS121
				225	-	1250	1125	33.2	7.5	167	-	1134	1020	32.3	7.3	156	
				450	1x	2372	2134	35.0	15.8	151	0.28	2135	1921	34.1	15.3	139	
				675	1.5x	3428	3084	36.3	24.5	140	-	3002	2701	35.4	23.9	126	
				900	2x	4373	3934	37.5	33.8	130	0.35	3756	3379	36.6	32.9	114	
Vero SE 13	BXRC-30E2000-C-7x-SE	3000K	80	158	-	897	807	32.3	5.1	176	-	848	763	31.4	5.0	171	DS121
				315	-	1736	1562	33.2	10.5	166	-	1635	1471	32.3	10.2	161	
				630	1x	3319	2987	35.0	22.1	151	0.20	2987	2688	34.1	21.5	139	
				945	1.5x	4764	4287	36.4	34.4	138	-	4453	4008	35.5	33.6	133	
				1260	2x	6080	5472	37.8	47.6	128	0.24	5665	5098	36.9	46.5	122	
Vero SE 13	BXRC-30E2000-D-7x-SE	3000K	80	125	-	639	575	29.6	3.7	173	-	611	549	28.7	3.6	170	DS121
				250	-	1239	1115	30.3	7.6	164	-	1180	1062	29.4	7.4	161	
				500	1x	2415	2173	31.8	15.9	152	0.34	2174	1956	30.9	15.5	141	
				750	1.5x	3413	3071	33.2	24.9	137	-	3233	2909	32.3	24.2	133	
				1000	2x	4364	3926	34.4	34.4	127	0.41	4124	3710	33.5	33.5	123	
Vero SE 13	BXRC-30G2000-B-7x-SE	3000K	90	135	-	536	482	32.3	4.4	123	-	491	442	31.4	4.2	116	DS121
				180	-	1037	934	33.2	6.0	174	-	941	847	32.3	5.8	162	
				270	1x	1968	1771	35.0	9.5	208	0.28	1771	1594	34.1	9.2	192	
				405	1.5x	2844	2559	36.3	14.7	193	-	2491	2241	35.4	14.3	174	
				540	2x	3628	3265	37.5	20.3	179	0.35	3116	2804	36.6	19.8	158	
Vero SE 13	BXRC-30G2000-C-7x-SE	3000K	90	135	-	744	670	32.3	4.4	171	-	704	633	31.4	4.2	166	DS121
				180	-	1441	1297	33.2	6.0	241	-	1357	1221	32.3	5.8	233	
				270	1x	2755	2479	35.0	9.5	292	0.20	2480	2231	34.1	9.2	269	
				405	1.5x	3954	3558	36.4	14.7	268	-	3697	3326	35.5	14.4	257	
				540	2x	5047	4541	37.8	20.4	247	0.24	4702	4231	36.9	19.9	236	
Vero SE 13	BXRC-30G2000-D-7x-SE	3000K	90	125	-	530	477	29.6	3.7	143	-	507	456	28.7	3.6	141	DS121
				250	-	1028	925	30.3	7.6	136	-	979	881	29.4	7.4	133	
				500	1x	2004	1803	31.8	15.9	126	0.34	1804	1623	30.9	15.5	117	
				750	1.5x	2832	2548	33.2	24.9	114	-	2683	2414	32.3	24.2	111	
				1000	2x	3621	3258	34.4	34.4	105	0.41	3422	3079	33.5	33.5	102	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Vero SE 13	BXRC-35E2000-B-7x-SE	3500K	80	113	-	665	599	32.3	3.6	182	-	609	549	31.4	3.5	172	DS121
				225	-	1287	1159	33.2	7.5	172	-	1167	1051	32.3	7.3	161	
				450	1x	2442	2198	35.0	15.8	155	0.28	2198	1978	34.1	15.3	143	
				675	1.5x	3529	3176	36.3	24.5	144	-	3091	2782	35.4	23.9	129	
				900	2x	4502	4052	37.5	33.8	133	0.35	3867	3480	36.6	32.9	117	
Vero SE 13	BXRC-35E2000-C-7x-SE	3500K	80	158	-	924	831	32.3	5.1	181	-	873	786	31.4	5.0	176	DS121
				315	-	1788	1609	33.2	10.5	171	-	1684	1516	32.3	10.2	165	
				630	1x	3419	3077	35.0	22.1	155	0.20	3077	2769	34.1	21.5	143	
				945	1.5x	4907	4416	36.4	34.4	143	-	4588	4129	35.5	33.6	137	
				1260	2x	6263	5637	37.8	47.6	132	0.24	5836	5252	36.9	46.5	125	
Vero SE 13	BXRC-35E2000-D-7x-SE	3500K	80	125	-	658	592	29.6	3.7	178	-	629	566	28.7	3.6	175	DS121
				250	-	1276	1148	30.3	7.6	168	-	1216	1094	29.4	7.4	165	
				500	1x	2487	2238	31.8	15.9	156	0.34	2238	2014	30.9	15.5	145	
				750	1.5x	3515	3163	33.2	24.9	141	-	3329	2996	32.3	24.2	137	
				1000	2x	4494	4044	34.4	34.4	131	0.41	4247	3821	33.5	33.5	127	
Vero SE 13	BXRC-35G2000-B-7x-SE	3500K	90	113	-	555	500	32.3	3.6	152	-	509	458	31.4	3.5	143	DS121
				225	-	1075	968	33.2	7.5	144	-	975	878	32.3	7.3	134	
				450	1x	2039	1836	35.0	15.8	129	0.28	1835	1652	34.1	15.3	120	
				675	1.5x	2947	2653	36.3	24.5	120	-	2581	2324	35.4	23.9	108	
				900	2x	3759	3384	37.5	33.8	111	0.35	3229	2907	36.6	32.9	98	
Vero SE 13	BXRC-35G2000-C-7x-SE	3500K	90	158	-	771	694	32.3	5.1	151	-	729	656	31.4	5.0	147	DS121
				315	-	1493	1344	33.2	10.5	143	-	1406	1265	32.3	10.2	138	
				630	1x	2854	2569	35.0	22.1	129	0.20	2569	2312	34.1	21.5	119	
				945	1.5x	4096	3687	36.4	34.4	119	-	3829	3447	35.5	33.6	114	
				1260	2x	5228	4706	37.8	47.6	110	0.24	4871	4385	36.9	46.5	105	
Vero SE 13	BXRC-35G2000-D-7x-SE	3500K	90	125	-	550	495	29.6	3.7	149	-	525	473	28.7	3.6	146	DS121
				250	-	1065	959	30.3	7.6	141	-	1015	913	29.4	7.4	138	
				500	1x	2076	1869	31.8	15.9	131	0.34	1868	1682	30.9	15.5	121	
				750	1.5x	2934	2641	33.2	24.9	118	-	2779	2502	32.3	24.2	115	
				1000	2x	3751	3377	34.4	34.4	109	0.41	3545	3191	33.5	33.5	106	
Vero SE 13	BXRC-40E2000-B-7x-SE	4000K	80	113	-	672	605	32.3	3.6	184	-	615	554	31.4	3.5	173	DS121
				225	-	1300	1170	33.2	7.5	174	-	1179	1061	32.3	7.3	162	
				450	1x	2466	2220	35.0	15.8	157	0.28	2219	1998	34.1	15.3	145	
				675	1.5x	3564	3208	36.3	24.5	145	-	3121	2810	35.4	23.9	131	
				900	2x	4546	4092	37.5	33.8	135	0.35	3905	3515	36.6	32.9	119	
Vero SE 13	BXRC-40E2000-C-7x-SE	4000K	80	158	-	933	839	32.3	5.1	183	-	882	794	31.4	5.0	178	DS121
				315	-	1806	1625	33.2	10.5	173	-	1700	1530	32.3	10.2	167	
				630	1x	3452	3107	35.0	22.1	157	0.20	3107	2796	34.1	21.5	144	
				945	1.5x	4955	4459	36.4	34.4	144	-	4632	4169	35.5	33.6	138	
				1260	2x	6324	5692	37.8	47.6	133	0.24	5892	5303	36.9	46.5	127	
Vero SE 13	BXRC-40E2000-D-7x-SE	4000K	80	125	-	665	598	29.6	3.7	180	-	635	571	28.7	3.6	177	DS121
				250	-	1289	1160	30.3	7.6	170	-	1227	1105	29.4	7.4	167	
				500	1x	2511	2260	31.8	15.9	158	0.34	2260	2034	30.9	15.5	146	
				750	1.5x	3548	3194	33.2	24.9	143	-	3362	3026	32.3	24.2	139	
				1000	2x	4537	4084	34.4	34.4	132	0.41	4288	3859	33.5	33.5	128	
Vero SE 13	BXRC-40G2000-B-7x-SE	4000K	90	113	-	575	517	32.3	3.6	157	-	527	474	31.4	3.5	148	DS121
				225	-	1112	1001	33.2	7.5	149	-	1009	908	32.3	7.3	139	
				450	1x	2110	1899	35.0	15.8	134	0.28	1899	1709	34.1	15.3	124	
				675	1.5x	3049	2744	36.3	24.5	124	-	2670	2403	35.4	23.9	112	
				900	2x	3890	3501	37.5	33.8	115	0.35	3341	3007	36.6	32.9	101	
Vero SE 13	BXRC-40G2000-C-7x-SE	4000K	90	158	-	798	718	32.3	5.1	156	-	755	679	31.4	5.0	152	DS121
				315	-	1545	1391	33.2	10.5	148	-	1455	1310	32.3	10.2	143	
				630	1x	2954	2659	35.0	22.1	134	0.20	2659	2393	34.1	21.5	124	
				945	1.5x	4240	3816	36.4	34.4	123	-	3964	3568	35.5	33.6	118	
				1260	2x	5411	4871	37.8	47.6	114	0.24	5042	4539	36.9	46.5	108	
Vero SE 13	BXRC-40G2000-D-7x-SE	4000K	90	125	-	569	512	29.6	3.7	154	-	543	489	28.7	3.6	151	DS121
				250	-	1103	992	30.3	7.6	146	-	1050	945	29.4	7.4	143	
				500	1x	2149	1934	31.8	15.9	135	0.34	1934	1741	30.9	15.5	125	
				750	1.5x	3037	2733	33.2	24.9	122	-	2877	2589	32.3	24.2	119	
				1000	2x	3883	3495	34.4	34.4	113	0.41	3669	3302	33.5	33.5	110	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Vero SE 13	BXRC-50C2001-B-74-SE	5000K	70	113	-	736	662	32.3	3.6	202	-	675	607	31.4	3.5	190	DS121
				225	-	1425	1282	33.2	7.5	191	-	1292	1163	32.3	7.3	178	
				450	1x	2703	2432	35.0	15.8	172	0.28	2433	2189	34.1	15.3	159	
				675	1.5x	3906	3515	36.3	24.5	159	-	3421	3078	35.4	23.9	143	
				900	2x	4983	4483	37.5	33.8	148	0.35	4280	3851	36.6	32.9	130	
Vero SE 13	BXRC-50C2001-C-74-SE	5000K	70	158	-	1022	920	32.3	5.1	200	-	967	870	31.4	5.0	195	DS121
				315	-	1979	1782	33.2	10.5	189	-	1864	1678	32.3	10.2	183	
				630	1x	3784	3406	35.0	22.1	172	0.20	3406	3065	34.1	21.5	158	
				945	1.5x	5431	4889	36.4	34.4	158	-	5077	4570	35.5	33.6	151	
				1260	2x	6932	6239	37.8	47.6	146	0.24	6459	5814	36.9	46.5	139	
Vero SE 13	BXRC-50C2001-D-74-SE	5000K	70	125	-	728	656	29.6	3.7	197	-	696	626	28.7	3.6	194	DS121
				250	-	1412	1271	30.3	7.6	186	-	1345	1211	29.4	7.4	183	
				500	1x	2752	2477	31.8	15.9	173	0.34	2477	2229	30.9	15.5	160	
				750	1.5x	3889	3500	33.2	24.9	156	-	3684	3316	32.3	24.2	152	
				1000	2x	4973	4476	34.4	34.4	145	0.41	4699	4229	33.5	33.5	140	
Vero SE 13	BXRC-50E2001-B-74-SE	5000K	80	113	-	692	623	32.3	3.6	190	-	634	571	31.4	3.5	179	DS121
				225	-	1339	1206	33.2	7.5	179	-	1215	1093	32.3	7.3	167	
				450	1x	2541	2287	35.0	15.8	161	0.28	2287	2058	34.1	15.3	149	
				675	1.5x	3672	3305	36.3	24.5	150	-	3216	2894	35.4	23.9	135	
				900	2x	4684	4216	37.5	33.8	139	0.35	4023	3621	36.6	32.9	122	
Vero SE 13	BXRC-50E2001-C-74-SE	5000K	80	158	-	961	865	32.3	5.1	188	-	909	818	31.4	5.0	183	DS121
				315	-	1861	1674	33.2	10.5	178	-	1752	1577	32.3	10.2	172	
				630	1x	3557	3201	35.0	22.1	161	0.20	3201	2881	34.1	21.5	149	
				945	1.5x	5105	4594	36.4	34.4	148	-	4773	4295	35.5	33.6	142	
				1260	2x	6516	5864	37.8	47.6	137	0.24	6071	5464	36.9	46.5	130	
Vero SE 13	BXRC-50E2001-D-74-SE	5000K	80	125	-	685	616	29.6	3.7	185	-	654	589	28.7	3.6	182	DS121
				250	-	1328	1195	30.3	7.6	175	-	1264	1138	29.4	7.4	172	
				500	1x	2587	2328	31.8	15.9	163	0.34	2328	2095	30.9	15.5	151	
				750	1.5x	3656	3290	33.2	24.9	147	-	3463	3117	32.3	24.2	143	
				1000	2x	4674	4206	34.4	34.4	136	0.41	4417	3975	33.5	33.5	132	
Vero SE 13	BXRC-50G2001-B-74-SE	5000K	90	113	-	589	531	32.3	3.6	161	-	540	486	31.4	3.5	152	DS121
				225	-	1140	1027	33.2	7.5	153	-	1034	932	32.3	7.3	142	
				450	1x	2162	1949	35.0	15.8	137	0.28	1946	1754	34.1	15.3	127	
				675	1.5x	3124	2817	36.3	24.5	128	-	2736	2467	35.4	23.9	114	
				900	2x	3985	3593	37.5	33.8	118	0.35	3423	3086	36.6	32.9	104	
Vero SE 13	BXRC-50G2001-C-74-SE	5000K	90	158	-	818	736	32.3	5.1	160	-	773	696	31.4	5.0	156	DS121
				315	-	1583	1425	33.2	10.5	151	-	1491	1342	32.3	10.2	146	
				630	1x	3027	2724	35.0	22.1	137	0.20	2724	2452	34.1	21.5	127	
				945	1.5x	4345	3910	36.4	34.4	126	-	4062	3655	35.5	33.6	121	
				1260	2x	5545	4990	37.8	47.6	116	0.24	5167	4650	36.9	46.5	111	
Vero SE 13	BXRC-50G2001-D-74-SE	5000K	90	125	-	583	525	29.6	3.7	158	-	557	501	28.7	3.6	155	DS121
				250	-	1130	1017	30.3	7.6	149	-	1076	969	29.4	7.4	146	
				500	1x	2202	1982	31.8	15.9	138	0.34	1982	1784	30.9	15.5	128	
				750	1.5x	3112	2801	33.2	24.9	125	-	2948	2653	32.3	24.2	122	
				1000	2x	3979	3581	34.4	34.4	116	0.41	3760	3384	33.5	33.5	112	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Vero SE 13	BXRC-57C2001-B-74-SE	5700K	70	113	-	710	639	32.3	3.6	195	-	651	586	31.4	3.5	183	DS121
				225	-	1375	1237	33.2	7.5	184	-	1247	1122	32.3	7.3	172	
				450	1x	2608	2347	35.0	15.8	166	0.28	2347	2112	34.1	15.3	153	
				675	1.5x	3769	3392	36.3	24.5	154	-	3301	2970	35.4	23.9	138	
				900	2x	4808	4326	37.5	33.8	142	0.35	4130	3716	36.6	32.9	125	
Vero SE 13	BXRC-57C2001-C-74-SE	5700K	70	158	-	986	888	32.3	5.1	193	-	933	839	31.4	5.0	188	DS121
				315	-	1910	1719	33.2	10.5	183	-	1798	1619	32.3	10.2	177	
				630	1x	3651	3286	35.0	22.1	166	0.20	3286	2957	34.1	21.5	153	
				945	1.5x	5240	4716	36.4	34.4	152	-	4899	4409	35.5	33.6	146	
				1260	2x	6688	6020	37.8	47.6	140	0.24	6232	5609	36.9	46.5	134	
Vero SE 13	BXRC-57C2001-D-74-SE	5700K	70	125	-	703	633	29.6	3.7	190	-	671	604	28.7	3.6	187	DS121
				250	-	1363	1226	30.3	7.6	180	-	1298	1168	29.4	7.4	177	
				500	1x	2656	2390	31.8	15.9	167	0.34	2390	2151	30.9	15.5	155	
				750	1.5x	3753	3377	32.2	24.9	151	-	3556	3200	32.3	24.2	147	
				1000	2x	4799	4318	34.4	34.4	140	0.41	4535	4081	33.5	33.5	135	
Vero SE 13	BXRC-57E2001-B-74-SE	5700K	80	113	-	704	634	32.3	3.6	193	-	645	581	31.4	3.5	182	DS121
				225	-	1363	1227	33.2	7.5	182	-	1236	1113	32.3	7.3	170	
				450	1x	2585	2327	35.0	15.8	164	0.28	2327	2094	34.1	15.3	152	
				675	1.5x	3736	3363	36.3	24.5	152	-	3272	2945	35.4	23.9	137	
				900	2x	4765	4290	37.5	33.8	141	0.35	4093	3685	36.6	32.9	124	
Vero SE 13	BXRC-57E2001-C-74-SE	5700K	80	158	-	978	880	32.3	5.1	192	-	924	832	31.4	5.0	186	DS121
				315	-	1892	1703	33.2	10.5	181	-	1782	1604	32.3	10.2	175	
				630	1x	3618	3256	35.0	22.1	164	0.20	3256	2930	34.1	21.5	151	
				945	1.5x	5193	4673	36.4	34.4	151	-	4855	4369	35.5	33.6	145	
				1260	2x	6628	5965	37.8	47.6	139	0.24	6175	5558	36.9	46.5	133	
Vero SE 13	BXRC-57E2001-D-74-SE	5700K	80	125	-	697	627	29.6	3.7	188	-	665	599	28.7	3.6	185	DS121
				250	-	1351	1216	30.3	7.6	178	-	1286	1158	29.4	7.4	175	
				500	1x	2632	2369	31.8	15.9	166	0.34	2369	2132	30.9	15.5	153	
				750	1.5x	3719	3348	32.2	24.9	149	-	3524	3171	32.3	24.2	145	
				1000	2x	4756	4281	34.4	34.4	138	0.41	4494	4045	33.5	33.5	134	
Vero SE 13	BXRC-65C2001-B-74-SE	6500K	70	113	-	723	651	32.3	3.6	198	-	663	596	31.4	3.5	187	DS121
				225	-	1400	1260	33.2	7.5	187	-	1270	1143	32.3	7.3	175	
				450	1x	2656	2390	35.0	15.8	169	0.28	2390	2151	34.1	15.3	156	
				675	1.5x	3838	3454	36.3	24.5	157	-	3361	3025	35.4	23.9	141	
				900	2x	4896	4406	37.5	33.8	145	0.35	4206	3784	36.6	32.9	128	
Vero SE 13	BXRC-65C2001-C-74-SE	6500K	70	158	-	1004	904	32.3	5.1	197	-	949	854	31.4	5.0	191	DS121
				315	-	1944	1750	33.2	10.5	186	-	1831	1648	32.3	10.2	180	
				630	1x	3717	3345	35.0	22.1	169	0.20	3345	3011	34.1	21.5	156	
				945	1.5x	5335	4801	36.4	34.4	155	-	4987	4488	35.5	33.6	149	
				1260	2x	6809	6128	37.8	47.6	143	0.24	6344	5710	36.9	46.5	136	
Vero SE 13	BXRC-65C2001-D-74-SE	6500K	70	125	-	716	644	29.6	3.7	193	-	684	615	28.7	3.6	191	DS121
				250	-	1388	1248	30.3	7.6	183	-	1322	1189	29.4	7.4	180	
				500	1x	2704	2433	31.8	15.9	170	0.34	2434	2190	30.9	15.5	157	
				750	1.5x	3821	3438	33.2	24.9	153	-	3620	3257	32.3	24.2	149	
				1000	2x	4886	4396	34.4	34.4	142	0.41	4617	4154	33.5	33.5	138	
Vero SE 13	BXRC-65E2001-B-74-SE	6500K	80	113	-	717	645	32.3	3.6	196	-	657	591	31.4	3.5	185	DS121
				225	-	1387	1249	33.2	7.5	186	-	1258	1133	32.3	7.3	173	
				450	1x	2632	2369	35.0	15.8	167	0.28	2369	2132	34.1	15.3	154	
				675	1.5x	3804	3424	36.3	24.5	155	-	3331	2998	35.4	23.9	139	
				900	2x	4852	4367	37.5	33.8	144	0.35	4168	3751	36.6	32.9	126	
Vero SE 13	BXRC-65E2001-C-74-SE	6500K	80	158	-	995	896	32.3	5.1	195	-	941	847	31.4	5.0	189	DS121
				315	-	1927	1734	33.2	10.5	184	-	1815	1633	32.3	10.2	178	
				630	1x	3684	3315	35.0	22.1	167	0.20	3316	2984	34.1	21.5	154	
				945	1.5x	5288	4758	36.4	34.4	154	-	4943	4448	35.5	33.6	147	
				1260	2x	6749	6073	37.8	47.6	142	0.24	6288	5658	36.9	46.5	135	
Vero SE 13	BXRC-65E2001-D-74-SE	6500K	80	125	-	709	638	29.6	3.7	192	-	678	610	28.7	3.6	189	DS121
				250	-	1375	1238	30.3	7.6	182	-	1310	1179	29.4	7.4	178	
				500	1x	2680	2412	31.8	15.9	169	0.34	2412	2171	30.9	15.5	156	
				750	1.5x	3787	3409	33.2	24.9	152	-	3588	3229	32.3	24.2	148	
				1000	2x	4842	4358	34.4	34.4	141	0.41	4576	4118	33.5	33.5	137	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Vero SE 18	BXRC-27E4000-B-7x-SE	2700K	80	450	-	2461	2215	33.3	15.0	164	-	2212	1991	32.4	14.6	152	DS122
				600	-	3229	2906	33.9	20.3	159	-	2896	2606	33.0	19.8	146	
				900	1x	4584	4126	35.0	31.5	146	0.15	4126	3713	34.1	30.7	134	
				1350	1.5x	6818	6137	36.7	49.5	138	-	6007	5407	35.8	48.3	124	
Vero SE 18	BXRC-27E4000-C-7x-SE	2700K	80	1800	2x	8773	7897	38.0	68.4	128	0.19	7626	6864	37.1	66.8	114	
				585	-	3114	2802	33.4	19.5	159	-	2947	2652	32.7	19.1	154	
				780	-	4081	3672	34.0	26.5	154	-	3782	3403	33.3	25.9	146	
				1170	1x	5960	5363	35.0	41.0	146	0.11	5364	4827	34.3	40.1	134	
Vero SE 18	BXRC-27E4000-D-7x-SE	2700K	80	1755	1.5x	8574	7715	36.8	64.6	133	-	7547	6791	36.1	63.3	119	
				2340	2x	10998	9896	38.1	89.2	123	0.13	9479	8530	37.4	87.4	108	
				525	-	2374	2137	27.7	14.5	163	-	2204	1983	26.8	14.1	157	
				700	-	3087	2778	28.2	19.7	156	-	2829	2546	27.3	19.1	148	
Vero SE 18	BXRC-27G4000-B-7x-SE	2700K	90	1050	1x	4457	4011	29.0	30.5	146	0.16	4011	3610	28.1	29.5	136	
				1575	1.5x	6366	5729	30.4	47.9	133	-	5629	5066	29.5	46.5	121	
				2100	2x	8104	7293	31.5	66.2	123	0.19	7047	6342	30.6	64.3	110	
				450	-	2051	1846	33.3	15.0	137	-	1843	1659	32.4	14.6	126	
Vero SE 18	BXRC-27G4000-C-7x-SE	2700K	90	600	-	2690	2421	33.9	20.3	132	-	2413	2172	33.0	19.8	122	
				900	1x	3820	3438	35.0	31.5	121	0.15	3438	3094	34.1	30.7	112	
				1350	1.5x	5681	5113	36.7	49.5	115	-	5006	4505	35.8	48.3	104	
				1800	2x	7311	6580	38.0	68.4	107	0.19	6355	5720	37.1	66.8	95	
Vero SE 18	BXRC-27G4000-D-7x-SE	2700K	90	585	-	2595	2336	33.4	19.5	133	-	2456	2210	32.7	19.1	129	
				780	-	3401	3061	34.0	26.5	128	-	3152	2836	33.3	25.9	121	
				1170	1x	4967	4470	35.0	41.0	121	0.11	4470	4023	34.3	40.1	111	
				1755	1.5x	7146	6431	36.8	64.6	111	-	6289	5660	36.1	63.3	99	
Vero SE 18	BXRC-27G4000-D-7x-SE	2700K	90	2340	2x	9166	8249	38.1	89.2	103	0.13	7900	7109	37.4	87.4	90	
				525	-	1978	1781	27.7	14.5	136	-	1836	1653	26.8	14.1	130	
				700	-	2573	2316	28.2	19.7	130	-	2358	2122	27.3	19.1	123	
				1050	1x	3714	3343	29.0	30.5	122	0.16	3343	3009	28.1	29.5	113	
Vero SE 18	BXRC-30E4000-B-7x-SE	3000K	80	1575	1.5x	5305	4775	30.4	47.9	111	-	4691	4222	29.5	46.5	101	
				2100	2x	6753	6079	31.5	66.2	102	0.19	5873	5286	30.6	64.3	91	
				450	-	2587	2307	33.3	15.0	173	-	2325	2073	32.4	14.6	159	
				600	-	3394	3026	33.9	20.3	167	-	3044	2714	33.0	19.8	154	
Vero SE 18	BXRC-30E4000-C-7x-SE	3000K	80	900	1x	4819	4297	35.0	31.5	153	0.15	4337	3867	34.1	30.7	141	
				1350	1.5x	7167	6391	36.7	49.5	145	-	6315	5631	35.8	48.3	131	
				1800	2x	9223	8224	38.0	68.4	135	0.19	8017	7149	37.1	66.8	120	
				585	-	3273	2919	33.4	19.5	168	-	3098	2763	32.7	19.1	162	
Vero SE 18	BXRC-30E4000-D-7x-SE	3000K	80	780	-	4290	3825	34.0	26.5	162	-	3975	3545	33.3	25.9	153	
				1170	1x	6265	5587	35.0	41.0	153	0.11	5639	5028	34.3	40.1	141	
				1755	1.5x	9013	8037	36.8	64.6	140	-	7933	7074	36.1	63.3	125	
				2340	2x	11561	10310	38.1	89.2	130	0.13	9964	8886	37.4	87.4	114	
Vero SE 18	BXRC-30G4000-B-7x-SE	3000K	80	525	-	2481	2226	27.7	14.5	171	-	2303	2066	26.8	14.1	164	
				700	-	3227	2894	28.2	19.7	163	-	2957	2652	27.3	19.1	155	
				1050	1x	4658	4178	29.0	30.5	153	0.16	4192	3760	28.1	29.5	142	
				1575	1.5x	6653	5968	30.4	47.9	139	-	5883	5277	29.5	46.5	127	
Vero SE 18	BXRC-30G4000-C-7x-SE	3000K	90	2100	2x	8470	7597	31.5	66.2	128	0.19	7365	6606	30.6	64.3	115	
				450	-	2128	1915	33.3	15.0	142	-	1912	1721	32.4	14.6	131	
				600	-	2791	2512	33.9	20.3	137	-	2503	2253	33.0	19.8	126	
				900	1x	3963	3567	35.0	31.5	126	0.15	3567	3210	34.1	30.7	116	
Vero SE 18	BXRC-30G4000-D-7x-SE	3000K	90	1350	1.5x	5894	5305	36.7	49.5	119	-	5193	4674	35.8	48.3	107	
				1800	2x	7585	6827	38.0	68.4	111	0.19	6593	5934	37.1	66.8	99	
				585	-	2692	2423	33.4	19.5	138	-	2548	2293	32.7	19.1	133	
				780	-	3528	3176	34.0	26.5	133	-	3270	2943	33.3	25.9	126	
Vero SE 18	BXRC-30G4000-D-7x-SE	3000K	90	1170	1x	5153	4638	35.0	41.0	126	0.11	4638	4174	34.3	40.1	116	
				1755	1.5x	7413	6672	36.8	64.6	115	-	6525	5873	36.1	63.3	103	
				2340	2x	9509	8559	38.1	89.2	107	0.13	8196	7377	37.4	87.4	94	
				525	-	2053	1847	27.7	14.5	141	-	1905	1714	26.8	14.1	135	
Vero SE 18	BXRC-30G4000-D-7x-SE	3000K	90	700	-	2669	2402	28.2	19.7	135	-	2446	2201	27.3	19.1	128	
				1050	1x	3853	3467	29.0	30.5	127	0.16	3468	3120	28.1	29.5	118	
				1575	1.5x	5503	4952	30.4	47.9	115	-	4867	4379	29.5	46.5	105	
				2100	2x	7006	6304	31.5	66.2	106	0.19	6092	5482	30.6	64.3	95	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _e 25°C (lm)	Minimum Pulsed Flux T _e 25°C (lm)	V _f T _e 25°C (V)	Power T _e 25°C (W)	Typical Efficacy T _e 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _e 85°C (lm)	Minimum DC Flux T _e 85°C (lm)	V _f T _e 85°C (V)	Power T _e 85°C (W)	Typical Efficacy T _e 85°C (lm/W)	Data Sheet
Vero SE 18	BXRC-35E4000-B-7x-SE	3500K	80	450	-	2640	2376	33.3	15.0	176	-	2373	2135	32.4	14.6	163	DS122
				600	-	3464	3117	33.9	20.3	170	-	3107	2796	33.0	19.8	157	
				900	1x	4918	4426	35.0	31.5	156	0.15	4426	3983	34.1	30.7	144	
				1350	1.5x	7315	6583	36.7	49.5	148	-	6445	5800	35.8	48.3	133	
Vero SE 18	BXRC-35E4000-C-7x-SE	3500K	80	1800	2x	9413	8471	38.0	68.4	138	0.19	8182	7364	37.1	66.8	123	DS122
				585	-	3341	3007	33.4	19.5	171	-	3162	2846	32.7	19.1	165	
				780	-	4378	3940	34.0	26.5	165	-	4057	3652	33.3	25.9	156	
				1170	1x	6394	5755	35.0	41.0	156	0.11	5755	5180	34.3	40.1	144	
Vero SE 18	BXRC-35E4000-D-7x-SE	3500K	80	1755	1.5x	9198	8279	36.8	64.6	142	-	8096	7287	36.1	63.3	128	DS122
				2340	2x	11799	10620	38.1	89.2	132	0.13	10169	9153	37.4	87.4	116	
				525	-	2547	2292	27.7	14.5	175	-	2364	2128	26.8	14.1	168	
				700	-	3312	2981	28.2	19.7	168	-	3036	2732	27.3	19.1	159	
Vero SE 18	BXRC-35E4000-B-7x-SE	3500K	90	1050	1x	4782	4303	29.0	30.5	157	0.16	4304	3873	28.1	29.5	146	DS122
				1575	1.5x	6830	6146	30.4	47.9	143	-	6040	5435	29.5	46.5	130	
				2100	2x	8695	7824	31.5	66.2	131	0.19	7511	6804	30.6	64.3	118	
				450	-	2205	1984	33.3	15.0	147	-	1981	1783	32.4	14.6	136	
Vero SE 18	BXRC-35G4000-B-7x-SE	3500K	90	600	-	2892	2602	33.9	20.3	142	-	2594	2334	33.0	19.8	131	DS122
				900	1x	4106	3695	35.0	31.5	130	0.15	3695	3326	34.1	30.7	120	
				1350	1.5x	6107	5496	36.7	49.5	123	-	5381	4842	35.8	48.3	111	
				1800	2x	7858	7072	38.0	68.4	115	0.19	6831	6147	37.1	66.8	102	
Vero SE 18	BXRC-35G4000-C-7x-SE	3500K	90	585	-	2790	2511	33.4	19.5	143	-	2640	2376	32.7	19.1	138	DS122
				780	-	3656	3290	34.0	26.5	138	-	3388	3049	33.3	25.9	131	
				1170	1x	5339	4805	35.0	41.0	130	0.11	4805	4325	34.3	40.1	120	
				1755	1.5x	7681	6912	36.8	64.6	119	-	6760	6084	36.1	63.3	107	
Vero SE 18	BXRC-35G4000-D-7x-SE	3500K	90	2340	2x	9852	8867	38.1	89.2	111	0.13	8491	7642	37.4	87.4	97	DS122
				525	-	2127	1914	27.7	14.5	146	-	1974	1777	26.8	14.1	140	
				700	-	2765	2489	28.2	19.7	140	-	2534	2281	27.3	19.1	133	
				1050	1x	3992	3593	29.0	30.5	131	0.16	3593	3234	28.1	29.5	122	
Vero SE 18	BXRC-40E4000-B-7x-SE	4000K	80	1575	1.5x	5702	5132	30.4	47.9	119	-	5042	4538	29.5	46.5	108	DS122
				2100	2x	7259	6533	31.5	66.2	110	0.19	6312	5681	30.6	64.3	98	
				450	-	2666	2399	33.3	15.0	178	-	2396	2156	32.4	14.6	164	
				600	-	3498	3148	33.9	20.3	172	-	3137	2823	33.0	19.8	158	
Vero SE 18	BXRC-40E4000-C-7x-SE	4000K	80	900	1x	4966	4469	35.0	31.5	158	0.15	4469	4022	34.1	30.7	146	DS122
				1350	1.5x	7386	6647	36.7	49.5	149	-	6508	5856	35.8	48.3	135	
				1800	2x	9504	8553	38.0	68.4	139	0.19	8262	7435	37.1	66.8	124	
				585	-	3373	3036	33.4	19.5	173	-	3192	2873	32.7	19.1	167	
Vero SE 18	BXRC-40E4000-D-7x-SE	4000K	80	780	-	4420	3978	34.0	26.5	167	-	4096	3686	33.3	25.9	158	DS122
				1170	1x	6456	5810	35.0	41.0	158	0.11	5810	5229	34.3	40.1	145	
				1755	1.5x	9288	8358	36.8	64.6	144	-	8175	7357	36.1	63.3	129	
				2340	2x	11913	10721	38.1	89.2	134	0.13	10268	9241	37.4	87.4	117	
Vero SE 18	BXRC-40E4000-B-7x-SE	4000K	90	525	-	2572	2315	27.7	14.5	177	-	2387	2148	26.8	14.1	170	DS122
				700	-	3344	3010	28.2	19.7	169	-	3065	2758	27.3	19.1	160	
				1050	1x	4828	4345	29.0	30.5	159	0.16	4345	3911	28.1	29.5	147	
				1575	1.5x	6896	6206	30.4	47.9	144	-	6098	5488	29.5	46.5	131	
Vero SE 18	BXRC-40G4000-B-7x-SE	4000K	90	2100	2x	8779	7901	31.5	66.2	133	0.19	7634	6870	30.6	64.3	119	DS122
				450	-	2281	2054	33.3	15.0	152	-	2050	1845	32.4	14.6	141	
				600	-	2993	2694	33.9	20.3	147	-	2684	2416	33.0	19.8	136	
				900	1x	4249	3825	35.0	31.5	135	0.15	3824	3443	34.1	30.7	125	
Vero SE 18	BXRC-40G4000-C-7x-SE	4000K	90	1350	1.5x	6320	5689	36.7	49.5	128	-	5568	5012	35.8	48.3	115	DS122
				1800	2x	8132	7321	38.0	68.4	119	0.19	7069	6364	37.1	66.8	106	
				585	-	2887	2598	33.4	19.5	148	-	2732	2459	32.7	19.1	143	
				780	-	3783	3405	34.0	26.5	143	-	3506	3155	33.3	25.9	135	
Vero SE 18	BXRC-40G4000-D-7x-SE	4000K	90	1170	1x	5525	4973	35.0	41.0	135	0.11	4973	4476	34.3	40.1	124	DS122
				1755	1.5x	7948	7154	36.8	64.6	123	-	6996	6297	36.1	63.3	111	
				2340	2x	10195	9177	38.1	89.2	114	0.13	8787	7909	37.4	87.4	100	
				525	-	2201	1981	27.7	14.5	151	-	2043	1838	26.8	14.1	145	
Vero SE 18	BXRC-40G4000-B-7x-SE	4000K	90	700	-	2862	2575	28.2	19.7	145	-	2623	2360	27.3	19.1	137	DS122
				1050	1x	4132	3718	29.0	30.5	136	0.16	3719	3346	28.1	29.5	126	
				1575	1.5x	5902	5311	30.4	47.9	123	-	5219	4696	29.5	46.5	112	
				2100	2x	7513	6760	31.5	66.2	114	0.19	6534	5879	30.6	64.3	102	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Vero SE 18	BXRC-50C4001-B-74-SE	5000K	70	450	-	2922	2630	33.3	15.0	195	-	2626	2363	32.4	14.6	180	DS122
				600	-	3834	3450	33.9	20.3	188	-	3438	3094	33.0	19.8	174	
				900	1x	5443	4898	35.0	31.5	173	0.15	4899	4408	34.1	30.7	160	
				1350	1.5x	8095	7285	36.7	49.5	163	-	7133	6419	35.8	48.3	148	
				1800	2x	10417	9374	38.0	68.4	152	0.19	9056	8149	37.1	66.8	136	
Vero SE 18	BXRC-50C4001-C-74-SE	5000K	70	585	-	3698	3328	33.4	19.5	189	-	3499	3149	32.7	19.1	183	DS122
				780	-	4845	4361	34.0	26.5	183	-	4490	4041	33.3	25.9	173	
				1170	1x	7077	6369	35.0	41.0	173	0.11	6369	5732	34.3	40.1	159	
				1755	1.5x	10181	9162	36.8	64.6	158	-	8961	8064	36.1	63.3	142	
				2340	2x	13059	11753	38.1	89.2	146	0.13	11256	10130	37.4	87.4	129	
Vero SE 18	BXRC-50C4001-D-74-SE	5000K	70	525	-	2819	2537	27.7	14.5	194	-	2617	2355	26.8	14.1	186	DS122
				700	-	3666	3299	28.2	19.7	186	-	3359	3024	27.3	19.1	176	
				1050	1x	5292	4763	29.0	30.5	174	0.16	4763	4287	28.1	29.5	161	
				1575	1.5x	7559	6803	30.4	47.9	158	-	6684	6016	29.5	46.5	144	
				2100	2x	9622	8661	31.5	66.2	145	0.19	8368	7531	30.6	64.3	130	
Vero SE 18	BXRC-50E4001-B-74-SE	5000K	80	450	-	2747	2472	33.3	15.0	183	-	2469	2222	32.4	14.6	169	DS122
				600	-	3604	3243	33.9	20.3	177	-	3232	2909	33.0	19.8	163	
				900	1x	5117	4605	35.0	31.5	162	0.15	4605	4145	34.1	30.7	150	
				1350	1.5x	7611	6849	36.7	49.5	154	-	6706	6035	35.8	48.3	139	
				1800	2x	9793	8814	38.0	68.4	143	0.19	8513	7661	37.1	66.8	127	
Vero SE 18	BXRC-50E4001-C-74-SE	5000K	80	585	-	3476	3128	33.4	19.5	178	-	3290	2960	32.7	19.1	172	DS122
				780	-	4555	4099	34.0	26.5	172	-	4221	3799	33.3	25.9	163	
				1170	1x	6653	5987	35.0	41.0	162	0.11	5988	5388	34.3	40.1	149	
				1755	1.5x	9571	8613	36.8	64.6	148	-	8424	7581	36.1	63.3	133	
				2340	2x	12277	11048	38.1	89.2	138	0.13	10581	9522	37.4	87.4	121	
Vero SE 18	BXRC-50E4001-D-74-SE	5000K	80	525	-	2650	2385	27.7	14.5	182	-	2460	2214	26.8	14.1	175	DS122
				700	-	3446	3101	28.2	19.7	175	-	3158	2842	27.3	19.1	165	
				1050	1x	4975	4477	29.0	30.5	163	0.16	4478	4029	28.1	29.5	152	
				1575	1.5x	7106	6395	30.4	47.9	148	-	6284	5655	29.5	46.5	135	
				2100	2x	9046	8141	31.5	66.2	137	0.19	7866	7079	30.6	64.3	122	
Vero SE 18	BXRC-50G4001-B-74-SE	5000K	90	450	-	2338	2104	33.3	15.0	156	-	2101	1891	32.4	14.6	144	DS122
				600	-	3067	2760	33.9	20.3	151	-	2750	2476	33.0	19.8	139	
				900	1x	4354	3919	35.0	31.5	138	0.15	3919	3527	34.1	30.7	128	
				1350	1.5x	6476	5829	36.7	49.5	131	-	5706	5136	35.8	48.3	118	
				1800	2x	8333	7501	38.0	68.4	122	0.19	7244	6520	37.1	66.8	108	
Vero SE 18	BXRC-50G4001-C-74-SE	5000K	90	585	-	2958	2663	33.4	19.5	151	-	2800	2520	32.7	19.1	146	DS122
				780	-	3877	3489	34.0	26.5	146	-	3593	3233	33.3	25.9	138	
				1170	1x	5662	5096	35.0	41.0	138	0.11	5096	4586	34.3	40.1	127	
				1755	1.5x	8145	7331	36.8	64.6	126	-	7169	6453	36.1	63.3	113	
				2340	2x	10448	9404	38.1	89.2	117	0.13	9005	8105	37.4	87.4	103	
Vero SE 18	BXRC-50G4001-D-74-SE	5000K	90	525	-	2255	2030	27.7	14.5	155	-	2094	1884	26.8	14.1	149	DS122
				700	-	2933	2640	28.2	19.7	149	-	2688	2419	27.3	19.1	141	
				1050	1x	4234	3811	29.0	30.5	139	0.16	3811	3430	28.1	29.5	129	
				1575	1.5x	6048	5443	30.4	47.9	126	-	5348	4813	29.5	46.5	115	
				2100	2x	7699	6930	31.5	66.2	116	0.19	6695	6026	30.6	64.3	104	
Vero SE 18	BXRC-57C4001-B-74-SE	5700K	70	450	-	2820	2538	33.3	15.0	188	-	2534	2281	32.4	14.6	174	DS122
				600	-	3699	3329	33.9	20.3	182	-	3318	2986	33.0	19.8	168	
				900	1x	5252	4727	35.0	31.5	167	0.15	4727	4254	34.1	30.7	154	
				1350	1.5x	7811	7030	36.7	49.5	158	-	6882	6194	35.8	48.3	142	
				1800	2x	10052	9047	38.0	68.4	147	0.19	8738	7864	37.1	66.8	131	
Vero SE 18	BXRC-57C4001-C-74-SE	5700K	70	585	-	3568	3211	33.4	19.5	183	-	3377	3039	32.7	19.1	177	DS122
				780	-	4676	4208	34.0	26.5	176	-	4333	3900	33.3	25.9	167	
				1170	1x	6829	6146	35.0	41.0	167	0.11	6146	5531	34.3	40.1	153	
				1755	1.5x	9824	8842	36.8	64.6	152	-	8647	7782	36.1	63.3	137	
				2340	2x	12602	11341	38.1	89.2	141	0.13	10861	9775	37.4	87.4	124	
Vero SE 18	BXRC-57C4001-D-74-SE	5700K	70	525	-	2721	2448	27.7	14.5	187	-	2525	2272	26.8	14.1	179	DS122
				700	-	3538	3183	28.2	19.7	179	-	3242	2917	27.3	19.1	170	
				1050	1x	5107	4595	29.0	30.5	168	0.16	4596	4136	28.1	29.5	156	
				1575	1.5x	7295	6563	30.4	47.9	152	-	6450	5804	29.5	46.5	139	
				2100	2x	9286	8355	31.5	66.2	140	0.19	8075	7266	30.6	64.3	126	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Vero SE 18	BXRC-57E4001-B-74-SE	5700K	80	450	-	2794	2515	33.3	15.0	186	-	2511	2260	32.4	14.6	172	DS122
				600	-	3665	3299	33.9	20.3	180	-	3287	2959	33.0	19.8	166	
				900	1x	5204	4684	35.0	31.5	165	0.15	4684	4216	34.1	30.7	153	
				1350	1.5x	7740	6967	36.7	49.5	156	-	6820	6138	35.8	48.3	141	
				1800	2x	9960	8965	38.0	68.4	146	0.19	8658	7793	37.1	66.8	130	
Vero SE 18	BXRC-57E4001-C-74-SE	5700K	80	585	-	3536	3182	33.4	19.5	181	-	3346	3011	32.7	19.1	175	DS122
				780	-	4633	4170	34.0	26.5	175	-	4294	3864	33.3	25.9	165	
				1170	1x	6767	6090	35.0	41.0	165	0.11	6090	5481	34.3	40.1	152	
				1755	1.5x	9735	8761	36.8	64.6	151	-	8568	7711	36.1	63.3	135	
				2340	2x	12487	11238	38.1	89.2	140	0.13	10763	9686	37.4	87.4	123	
Vero SE 18	BXRC-57E4001-D-74-SE	5700K	80	525	-	2695	2426	27.7	14.5	185	-	2502	2252	26.8	14.1	178	DS122
				700	-	3505	3155	28.2	19.7	178	-	3212	2891	27.3	19.1	168	
				1050	1x	5060	4554	29.0	30.5	166	0.16	4554	4099	28.1	29.5	154	
				1575	1.5x	7227	6505	30.4	47.9	151	-	6391	5752	29.5	46.5	138	
				2100	2x	9201	8281	31.5	66.2	139	0.19	8001	7201	30.6	64.3	124	
Vero SE 18	BXRC-65C4001-B-74-SE	6500K	70	450	-	2871	2584	33.3	15.0	192	-	2580	2322	32.4	14.6	177	DS122
				600	-	3767	3390	33.9	20.3	185	-	3378	3040	33.0	19.8	171	
				900	1x	5348	4813	35.0	31.5	170	0.15	4813	4332	34.1	30.7	157	
				1350	1.5x	7954	7158	36.7	49.5	161	-	7008	6307	35.8	48.3	145	
				1800	2x	10236	9212	38.0	68.4	150	0.19	8897	8007	37.1	66.8	133	
Vero SE 18	BXRC-65C4001-C-74-SE	6500K	70	585	-	3633	3270	33.4	19.5	186	-	3438	3094	32.7	19.1	180	DS122
				780	-	4761	4285	34.0	26.5	180	-	4412	3971	33.3	25.9	170	
				1170	1x	6953	6258	35.0	41.0	170	0.11	6258	5632	34.3	40.1	156	
				1755	1.5x	10003	9003	36.8	64.6	155	-	8804	7924	36.1	63.3	139	
				2340	2x	12831	11548	38.1	89.2	144	0.13	11058	9953	37.4	87.4	126	
Vero SE 18	BXRC-65C4001-D-74-SE	6500K	70	525	-	2770	2493	27.7	14.5	190	-	2571	2314	26.8	14.1	183	DS122
				700	-	3601	3241	28.2	19.7	182	-	3300	2970	27.3	19.1	173	
				1050	1x	5199	4679	29.0	30.5	171	0.16	4679	4211	28.1	29.5	159	
				1575	1.5x	7426	6683	30.4	47.9	155	-	6567	5910	29.5	46.5	141	
				2100	2x	9453	8508	31.5	66.2	143	0.19	8221	7398	30.6	64.3	128	
Vero SE 18	BXRC-65E4001-B-74-SE	6500K	80	450	-	2846	2561	33.3	15.0	190	-	2557	2301	32.4	14.6	175	DS122
				600	-	3733	3360	33.9	20.3	184	-	3348	3013	33.0	19.8	169	
				900	1x	5300	4770	35.0	31.5	168	0.15	4770	4293	34.1	30.7	155	
				1350	1.5x	7883	7094	36.7	49.5	159	-	6945	6251	35.8	48.3	144	
				1800	2x	10144	9129	38.0	68.4	148	0.19	8818	7936	37.1	66.8	132	
Vero SE 18	BXRC-65E4001-C-74-SE	6500K	80	585	-	3600	3240	33.4	19.5	184	-	3407	3067	32.7	19.1	178	DS122
				780	-	4718	4246	34.0	26.5	178	-	4372	3935	33.3	25.9	168	
				1170	1x	6891	6202	35.0	41.0	168	0.11	6202	5582	34.3	40.1	155	
				1755	1.5x	9913	8922	36.8	64.6	153	-	8725	7853	36.1	63.3	138	
				2340	2x	12716	11445	38.1	89.2	143	0.13	10960	9864	37.4	87.4	125	
Vero SE 18	BXRC-65E4001-D-74-SE	6500K	80	525	-	2745	2471	27.7	14.5	189	-	2548	2293	26.8	14.1	181	DS122
				700	-	3569	3213	28.2	19.7	181	-	3271	2944	27.3	19.1	171	
				1050	1x	5153	4638	29.0	30.5	169	0.16	4638	4174	28.1	29.5	157	
				1575	1.5x	7360	6625	30.4	47.9	154	-	6508	5858	29.5	46.5	140	
				2100	2x	9370	8433	31.5	66.2	142	0.19	8148	7334	30.6	64.3	127	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T_c 25°C (lm)	Minimum Pulsed Flux T_c 25°C (lm)	Vf T_c 25°C (V)	Power T_c 25°C (W)	Typical Efficacy T_c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (°C/W)	Typical DC Flux T_c 85°C (lm)	Minimum DC Flux T_c 85°C (lm)	Vf T_c 85°C (V)	Power T_c 85°C (W)	Typical Efficacy T_c 85°C (lm/W)	Data Sheet
Vero SE 29	BXRC-35E10K0-B-7x-SE	3500K	80	900	-	7814	7033	49.6	44.6	175	-	7824	7042	48.3	43.4	180	DS123
				1200	-	10310	9279	50.5	60.6	170	-	9779	8801	49.2	59.0	166	
				1800	1x	14912	13421	52.0	93.6	159	0.06	13421	12079	50.7	91.2	147	
				2700	1.5x	21986	19788	54.1	146.1	151	-	18346	16512	52.8	142.5	129	
Vero SE 29	BXRC-35E10K0-C-7x-SE	3500K	80	3600	2x	28348	25513	55.8	200.9	141	0.07	22520	20268	54.5	196.1	115	DS123
				855	-	10730	9657	66.2	56.6	190	-	10211	9189	65.2	55.7	183	
				1140	-	13638	12273	67.3	76.7	178	-	12580	11322	66.3	75.5	167	
				1710	1x	18889	16999	69.4	118.7	159	0.04	17000	15299	68.4	116.9	145	
Vero SE 29	BXRC-35E10K0-D-7x-SE	3500K	80	2565	1.5x	26796	24115	72.1	184.9	145	-	23047	20741	71.1	182.3	126	DS123
				3420	2x	33587	30226	74.4	254.4	132	0.05	28222	25398	73.4	250.9	112	
				1050	-	6911	6221	35.4	37.2	186	-	6734	6061	34.1	35.8	188	
				1400	-	8895	8006	36.2	50.7	176	-	8278	7450	34.9	48.8	170	
Vero SE 29	BXRC-35G10K0-B-7x-SE	3500K	90	2100	1x	12565	11309	37.6	79.0	159	0.06	11309	10178	36.3	76.2	148	DS123
				3150	1.5x	17888	16100	39.5	124.4	144	-	15072	13566	38.2	120.2	125	
				4200	2x	22545	20292	41.2	173.0	130	0.07	18410	16570	39.9	167.5	110	
				900	-	6524	5872	49.6	44.6	146	-	6533	5880	48.3	43.4	150	
Vero SE 29	BXRC-35G10K0-C-7x-SE	3500K	90	1200	-	8609	7748	50.5	60.6	142	-	8165	7349	49.2	59.0	138	DS123
				1800	1x	12451	11206	52.0	93.6	133	0.06	11206	10085	50.7	91.2	123	
				2700	1.5x	18358	16522	54.1	146.1	126	-	15318	13787	52.8	142.5	108	
				3600	2x	23669	21303	55.8	200.9	118	0.07	18804	16923	54.5	196.1	96	
Vero SE 29	BXRC-35G10K0-D-7x-SE	3500K	90	855	-	8959	8063	66.2	56.6	158	-	8525	7673	65.2	55.7	153	DS123
				1140	-	11387	10248	67.3	76.7	148	-	10504	9453	66.3	75.5	139	
				1710	1x	15771	14194	69.4	118.7	133	0.04	14194	12775	68.4	116.9	121	
				2565	1.5x	22373	20136	72.1	184.9	121	-	19243	17318	71.1	182.3	106	
Vero SE 29	BXRC-40E10K0-B-7x-SE	4000K	80	3420	2x	28043	25238	74.4	254.4	110	0.05	23564	21207	73.4	250.9	94	DS123
				1050	-	5771	5194	35.4	37.2	155	-	5623	5060	34.1	35.8	157	
				1400	-	7427	6684	36.2	50.7	147	-	6911	6220	34.9	48.8	142	
				2100	1x	10491	9442	37.6	79.0	133	0.06	9442	8498	36.3	76.2	124	
Vero SE 29	BXRC-40E10K0-C-7x-SE	4000K	80	3150	1.5x	14936	13442	39.5	124.4	120	-	12584	11326	38.2	120.2	105	DS123
				4200	2x	18824	16942	41.2	173.0	109	0.07	15371	13834	39.9	167.5	92	
				900	-	7890	7101	49.6	44.6	177	-	7900	7110	48.3	43.4	182	
				1200	-	10410	9369	50.5	60.6	172	-	9874	8887	49.2	59.0	167	
Vero SE 29	BXRC-40E10K0-D-7x-SE	4000K	80	1800	1x	15057	13551	52.0	93.6	161	0.06	13551	12196	50.7	91.2	149	DS123
				2700	1.5x	22200	19980	54.1	146.1	152	-	18525	16672	52.8	142.5	130	
				3600	2x	28623	25760	55.8	200.9	142	0.07	22739	20465	54.5	196.1	116	
				855	-	10834	9751	66.2	56.6	191	-	10310	9279	65.2	55.7	185	
Vero SE 29	BXRC-40G10K0-B-7x-SE	4000K	90	1140	-	13770	12393	67.3	76.7	179	-	12702	11432	66.3	75.5	168	DS123
				1710	1x	19072	17165	69.4	118.7	161	0.04	17165	15449	68.4	116.9	147	
				2565	1.5x	27056	24351	72.1	184.9	146	-	23270	20943	71.1	182.3	128	
				3420	2x	33912	30521	74.4	254.4	133	0.05	28496	25646	73.4	250.9	114	
Vero SE 29	BXRC-40G10K0-C-7x-SE	4000K	80	1050	-	6978	6280	35.4	37.2	188	-	6800	6119	34.1	35.8	190	DS123
				1400	-	8981	8083	36.2	50.7	177	-	8358	7522	34.9	48.8	171	
				2100	1x	12687	11418	37.6	79.0	161	0.06	11418	10276	36.3	76.2	150	
				3150	1.5x	18062	16255	39.5	124.4	145	-	15219	13696	38.2	120.2	127	
Vero SE 29	BXRC-40G10K0-D-7x-SE	4000K	90	4200	2x	22764	20487	41.2	173.0	132	0.07	18589	16730	39.9	167.5	111	DS123
				900	-	6752	6077	49.6	44.6	151	-	6761	6085	48.3	43.4	156	
				1200	-	8909	8018	50.5	60.6	147	-	8450	7605	49.2	59.0	143	
				1800	1x	12885	11597	52.0	93.6	138	0.06	11597	10437	50.7	91.2	127	
Vero SE 29	BXRC-40G10K0-C-7x-SE	4000K	90	2700	1.5x	18998	17099	54.1	146.1	130	-	15852	14268	52.8	142.5	111	DS123
				3600	2x	24494	22046	55.8	200.9	122	0.07	19459	17514	54.5	196.1	99	
				855	-	9271	8344	66.2	56.6	164	-	8823	7940	65.2	55.7	158	
				1140	-	11784	10606	67.3	76.7	154	-	10870	9783	66.3	75.5	144	
Vero SE 29	BXRC-40G10K0-D-7x-SE	4000K	90	1710	1x	16321	14689	69.4	118.7	138	0.04	14689	13220	68.4	116.9	126	DS123
				2565	1.5x	23153	20838	72.1	184.9	125	-	19914	17922	71.1	182.3	109	
				3420	2x	29021	26119	74.4	254.4	114	0.05	24385	21947	73.4	250.9	97	
				1050	-	5972	5375	35.4	37.2	161	-	5819	5237	34.1	35.8	163	
Vero SE 29	BXRC-40G10K0-D-7x-SE	4000K	90	1400	-	7686	6918	36.2	50.7	152	-	7153	6438	34.9	48.8	146	DS123
				2100	1x	10857	9772	37.6	79.0	138	0.06	9771	8795	36.3	76.2	128	
				3150	1.5x	15457	13912	39.5	124.4	124	-	13024	11722	38.2	120.2	108	
				4200	2x	19481	17534	41.2	173.0	113	0.07	15908	14318	39.9	167.5	95	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Vero SE 29	BXRC-50C10K1-B-74-SE	5000K	70	900	-	8649	7784	49.6	44.6	194	-	8660	7794	48.3	43.4	199	DS123
				1200	-	11412	10271	50.5	60.6	188	-	10824	9742	49.2	59.0	183	
				1800	1x	16505	14855	52.0	93.6	176	0.06	14855	13370	50.7	91.2	163	
				2700	1.5x	24335	21902	54.1	146.1	167	-	20306	18276	52.8	142.5	143	
				3600	2x	31376	28239	55.8	200.9	156	0.07	24926	22434	54.5	196.1	127	
Vero SE 29	BXRC-50C10K1-C-74-SE	5000K	70	855	-	11876	10689	66.2	56.6	210	-	11301	10171	65.2	55.7	203	DS123
				1140	-	15094	13585	67.3	76.7	197	-	13924	12532	66.3	75.5	184	
				1710	1x	20906	18816	69.4	118.7	176	0.04	18815	16934	68.4	116.9	161	
				2565	1.5x	29658	26693	72.1	184.9	160	-	25508	22958	71.1	182.3	140	
				3420	2x	37173	33457	74.4	254.4	146	0.05	31236	28113	73.4	250.9	125	
Vero SE 29	BXRC-50C10K1-D-74-SE	5000K	70	1050	-	7650	6884	35.4	37.2	206	-	7453	6708	34.1	35.8	208	DS123
				1400	-	9845	8860	36.2	50.7	194	-	9162	8246	34.9	48.8	188	
				2100	1x	13907	12516	37.6	79.0	176	0.06	12516	11264	36.3	76.2	164	
				3150	1.5x	19799	17818	39.5	124.4	159	-	16682	15014	38.2	120.2	139	
				4200	2x	24953	22457	41.2	173.0	144	0.07	20377	18338	39.9	167.5	122	
Vero SE 29	BXRC-50E10K1-B-74-SE	5000K	80	900	-	8130	7317	49.6	44.6	182	-	8141	7326	48.3	43.4	187	DS123
				1200	-	10727	9654	50.5	60.6	177	-	10175	9157	49.2	59.0	172	
				1800	1x	15515	13963	52.0	93.6	166	0.06	13964	12567	50.7	91.2	153	
				2700	1.5x	22875	20587	54.1	146.1	157	-	19088	17179	52.8	142.5	134	
				3600	2x	29494	26544	55.8	200.9	147	0.07	23431	21087	54.5	196.1	119	
Vero SE 29	BXRC-50E10K1-C-74-SE	5000K	80	855	-	11164	10047	66.2	56.6	197	-	10623	9561	65.2	55.7	191	DS123
				1140	-	14189	12770	67.3	76.7	185	-	13088	11780	66.3	75.5	173	
				1710	1x	19652	17687	69.4	118.7	166	0.04	17687	15918	68.4	116.9	151	
				2565	1.5x	27879	25091	72.1	184.9	151	-	23978	21580	71.1	182.3	132	
				3420	2x	34943	31449	74.4	254.4	137	0.05	29362	26426	73.4	250.9	117	
Vero SE 29	BXRC-50E10K1-D-74-SE	5000K	80	1050	-	7190	6472	35.4	37.2	193	-	7006	6306	34.1	35.8	196	DS123
				1400	-	9254	8329	36.2	50.7	183	-	8612	7751	34.9	48.8	176	
				2100	1x	13072	11766	37.6	79.0	166	0.06	11765	10589	36.3	76.2	154	
				3150	1.5x	18610	16751	39.5	124.4	150	-	15681	14114	38.2	120.2	130	
				4200	2x	23455	21112	41.2	173.0	136	0.07	19153	17240	39.9	167.5	114	
Vero SE 29	BXRC-50G10K1-B-74-SE	5000K	90	900	-	6919	6227	49.6	44.6	155	-	6928	6235	48.3	43.4	159	DS123
				1200	-	9129	8216	50.5	60.6	151	-	8659	7793	49.2	59.0	147	
				1800	1x	13204	11883	52.0	93.6	141	0.06	11884	10695	50.7	91.2	130	
				2700	1.5x	19468	17520	54.1	146.1	133	-	16245	14620	52.8	142.5	114	
				3600	2x	25101	22590	55.8	200.9	125	0.07	19941	17946	54.5	196.1	102	
Vero SE 29	BXRC-50G10K1-C-74-SE	5000K	90	855	-	9501	8551	66.2	56.6	168	-	9041	8137	65.2	55.7	162	DS123
				1140	-	12076	10868	67.3	76.7	157	-	11139	10025	66.3	75.5	147	
				1710	1x	16725	15052	69.4	118.7	141	0.04	15053	13547	68.4	116.9	129	
				2565	1.5x	23726	21353	72.1	184.9	128	-	20407	18365	71.1	182.3	112	
				3420	2x	29739	26764	74.4	254.4	117	0.05	24989	22489	73.4	250.9	100	
Vero SE 29	BXRC-50G10K1-D-74-SE	5000K	90	1050	-	6119	5508	35.4	37.2	165	-	5962	5366	34.1	35.8	167	DS123
				1400	-	7875	7088	36.2	50.7	155	-	7329	6597	34.9	48.8	150	
				2100	1x	11125	10013	37.6	79.0	141	0.06	10013	9012	36.3	76.2	131	
				3150	1.5x	15838	14255	39.5	124.4	127	-	13345	12011	38.2	120.2	111	
				4200	2x	19962	17966	41.2	173.0	115	0.07	16300	14671	39.9	167.5	97	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	Vf T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	Vf T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Vero SE 29	BXRC-57C10K1-B-74-SE	5700K	70	900	-	8345	7510	49.6	44.6	187	-	8356	7521	48.3	43.4	192	DS123
				1200	-	11011	9910	50.5	60.6	182	-	10444	9400	49.2	59.0	177	
				1800	1x	15926	14333	52.0	93.6	170	0.06	14333	12900	50.7	91.2	157	
				2700	1.5x	23481	21133	54.1	146.1	161	-	19594	17634	52.8	142.5	138	
				3600	2x	30275	27247	55.8	200.9	151	0.07	24051	21646	54.5	196.1	123	
Vero SE 29	BXRC-57C10K1-C-74-SE	5700K	70	855	-	11459	10313	66.2	56.6	202	-	10904	9814	65.2	55.7	196	DS123
				1140	-	14564	13108	67.3	76.7	190	-	13435	12091	66.3	75.5	178	
				1710	1x	20172	18155	69.4	118.7	170	0.04	18155	16340	68.4	116.9	155	
				2565	1.5x	28616	25755	72.1	184.9	155	-	24612	22151	71.1	182.3	135	
				3420	2x	35868	32282	74.4	254.4	141	0.05	30139	27126	73.4	250.9	120	
Vero SE 29	BXRC-57C10K1-D-74-SE	5700K	70	1050	-	7381	6643	35.4	37.2	199	-	7192	6473	34.1	35.8	201	DS123
				1400	-	9499	8549	36.2	50.7	187	-	8840	7956	34.9	48.8	181	
				2100	1x	13419	12077	37.6	79.0	170	0.06	12077	10869	36.3	76.2	159	
				3150	1.5x	19104	17193	39.5	124.4	154	-	16097	14487	38.2	120.2	134	
				4200	2x	24078	21670	41.2	173.0	139	0.07	19662	17695	39.9	167.5	117	
Vero SE 29	BXRC-57E10K1-B-74-SE	5700K	80	900	-	8269	7442	49.6	44.6	185	-	8280	7452	48.3	43.4	191	DS123
				1200	-	10911	9819	50.5	60.6	180	-	10349	9314	49.2	59.0	175	
				1800	1x	15781	14202	52.0	93.6	169	0.06	14202	12782	50.7	91.2	156	
				2700	1.5x	23268	20939	54.1	146.1	159	-	19415	17473	52.8	142.5	136	
				3600	2x	30000	26998	55.8	200.9	149	0.07	23832	21448	54.5	196.1	122	
Vero SE 29	BXRC-57E10K1-C-74-SE	5700K	80	855	-	11355	10220	66.2	56.6	201	-	10805	9725	65.2	55.7	194	DS123
				1140	-	14432	12989	67.3	76.7	188	-	13313	11982	66.3	75.5	176	
				1710	1x	19989	17990	69.4	118.7	168	0.04	17990	16191	68.4	116.9	154	
				2565	1.5x	28357	25521	72.1	184.9	153	-	24389	21950	71.1	182.3	134	
				3420	2x	35543	31988	74.4	254.4	140	0.05	29866	26879	73.4	250.9	119	
Vero SE 29	BXRC-57E10K1-D-74-SE	5700K	80	1050	-	7314	6582	35.4	37.2	197	-	7127	6414	34.1	35.8	199	DS123
				1400	-	9413	8471	36.2	50.7	186	-	8760	7884	34.9	48.8	179	
				2100	1x	13297	11967	37.6	79.0	168	0.06	11967	10770	36.3	76.2	157	
				3150	1.5x	18930	17037	39.5	124.4	152	-	15950	14355	38.2	120.2	133	
				4200	2x	23859	21472	41.2	173.0	138	0.07	19483	17534	39.9	167.5	116	
Vero SE 29	BXRC-65C10K1-B-74-SE	6500K	70	900	-	8497	7647	49.6	44.6	190	-	8508	7657	48.3	43.4	196	DS123
				1200	-	11211	10090	50.5	60.6	185	-	10634	9570	49.2	59.0	180	
				1800	1x	16215	14593	52.0	93.6	173	0.06	14594	13134	50.7	91.2	160	
				2700	1.5x	23907	21516	54.1	146.1	164	-	19949	17954	52.8	142.5	140	
				3600	2x	30825	27741	55.8	200.9	153	0.07	24488	22038	54.5	196.1	125	
Vero SE 29	BXRC-65C10K1-C-74-SE	6500K	70	855	-	11668	10501	66.2	56.6	206	-	11103	9993	65.2	55.7	199	DS123
				1140	-	14829	13347	67.3	76.7	193	-	13679	12312	66.3	75.5	181	
				1710	1x	20539	18486	69.4	118.7	173	0.04	18485	16637	68.4	116.9	158	
				2565	1.5x	29137	26225	72.1	184.9	158	-	25060	22555	71.1	182.3	137	
				3420	2x	36521	32870	74.4	254.4	144	0.05	30687	27620	73.4	250.9	122	
Vero SE 29	BXRC-65C10K1-D-74-SE	6500K	70	1050	-	7515	6763	35.4	37.2	202	-	7323	6590	34.1	35.8	205	DS123
				1400	-	9672	8704	36.2	50.7	191	-	9001	8101	34.9	48.8	184	
				2100	1x	13663	12296	37.6	79.0	173	0.06	12297	11066	36.3	76.2	161	
				3150	1.5x	19451	17505	39.5	124.4	156	-	16389	14750	38.2	120.2	136	
				4200	2x	24516	22063	41.2	173.0	142	0.07	20019	18016	39.9	167.5	120	
Vero SE 29	BXRC-65E10K1-B-74-SE	6500K	80	900	-	8421	7579	49.6	44.6	189	-	8432	7589	48.3	43.4	194	DS123
				1200	-	11111	10000	50.5	60.6	183	-	10539	9485	49.2	59.0	179	
				1800	1x	16070	14464	52.0	93.6	172	0.06	14463	13018	50.7	91.2	159	
				2700	1.5x	23694	21326	54.1	146.1	162	-	19771	17795	52.8	142.5	139	
				3600	2x	30549	27496	55.8	200.9	152	0.07	24269	21844	54.5	196.1	124	
Vero SE 29	BXRC-65E10K1-C-74-SE	6500K	80	855	-	11564	10407	66.2	56.6	204	-	11004	9903	65.2	55.7	198	DS123
				1140	-	14697	13227	67.3	76.7	192	-	13557	12201	66.3	75.5	179	
				1710	1x	20356	18320	69.4	118.7	172	0.04	18320	16488	68.4	116.9	157	
				2565	1.5x	28877	25989	72.1	184.9	156	-	24837	22353	71.1	182.3	136	
				3420	2x	36195	32575	74.4	254.4	142	0.05	30414	27372	73.4	250.9	121	
Vero SE 29	BXRC-65E10K1-D-74-SE	6500K	80	1050	-	7448	6703	35.4	37.2	200	-	7257	6531	34.1	35.8	203	DS123
				1400	-	9586	8626	36.2	50.7	189	-	8921	8028	34.9	48.8	183	
				2100	1x	13541	12186	37.6	79.0	171	0.06	12187	10967	36.3	76.2	160	
				3150	1.5x	19278	17349	39.5	124.4	155	-	16243	14618	38.2	120.2	135	
				4200	2x	24297	21865	41.2	173.0	140	0.07	19840	17855	39.9	167.5	118	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (v)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Décor 10 Class A	BXRC-30A1001-B-73-SE	3000K	93	135	-	563	495	33.3	4.5	125	-	495	436	32.3	4.4	114	DS125
				180	0.75x	738	649	33.8	6.1	121	-	649	571	32.9	5.9	110	
				270	1x	1056	929	35.0	9.5	112	0.49	929	818	34.0	9.2	101	
				405	1.5x	1549	1363	36.4	14.8	105	-	1363	1199	35.5	14.4	95	
				540	2x	1985	1746	37.8	20.4	97	0.57	1747	1537	36.8	19.9	88	
Décor 10 Class A	BXRC-30A1001-C-73-SE	3000K	93	180	-	748	658	33.3	6.0	125	-	658	579	32.3	5.8	113	DS125
				240	0.75x	980	862	33.8	8.1	121	-	862	759	32.9	7.9	109	
				360	1x	1407	1238	35.0	12.6	112	0.37	1238	1089	34.0	12.3	101	
				540	1.5x	2049	1803	36.4	19.7	104	-	1803	1586	35.4	19.1	94	
				720	2x	2617	2303	37.7	27.1	96	0.43	2303	2026	36.7	26.4	87	
Décor 10 Class A	BXRC-30A1001-D-73-SE	3000K	93	175	-	548	482	24.9	4.4	126	-	482	424	24.2	4.2	114	DS125
				233	0.75x	719	633	25.4	5.9	122	-	632	557	24.7	5.7	110	
				350	1x	1026	903	26.0	9.1	113	0.49	903	795	25.3	8.9	102	
				525	1.5x	1510	1329	27.4	14.4	105	-	1329	1170	26.7	14.0	95	
				700	2x	1935	1703	28.4	19.9	97	0.57	1703	1499	27.7	19.4	88	
Décor 10 Class A	BXRC-35A1001-B-73-SE	3500K	93	135	-	606	533	33.3	4.5	135	-	533	469	32.3	4.4	122	DS125
				180	0.75x	794	699	33.8	6.1	130	-	699	615	32.9	5.9	118	
				270	1x	1137	1001	35.0	9.5	120	0.49	1001	881	34.0	9.2	109	
				405	1.5x	1668	1469	36.4	14.8	113	-	1468	1292	35.5	14.4	102	
				540	2x	2137	1881	37.8	20.4	105	0.57	1881	1656	36.8	19.9	95	
Décor 10 Class A	BXRC-35A1001-C-73-SE	3500K	93	180	-	806	710	33.3	6.0	135	-	709	625	32.3	5.8	122	DS125
				240	-	1056	930	33.8	8.1	130	-	929	818	32.9	7.9	118	
				360	1x	1516	1335	35.0	12.6	120	0.37	1334	1175	34.0	12.3	109	
				540	1.5x	2208	1944	36.4	19.7	112	-	1943	1711	35.4	19.1	102	
				720	2x	2820	2483	37.7	27.1	104	0.43	2481	2185	36.7	26.4	94	
Décor 10 Class A	BXRC-35A1001-D-73-SE	3500K	93	175	-	591	520	24.9	4.4	135	-	520	457	24.2	4.2	123	DS125
				233	-	775	682	25.4	5.9	131	-	682	600	24.7	5.7	119	
				350	1x	1106	973	26.0	9.1	122	0.49	973	856	25.3	8.9	110	
				525	1.5x	1628	1432	27.4	14.4	113	-	1433	1260	26.7	14.0	102	
				700	2x	2086	1835	28.4	19.9	105	0.57	1835	1615	27.7	19.4	95	
Décor 10 Class A	BXRC-40A1001-B-73-SE	4000K	93	135	-	645	568	33.3	4.5	144	-	567	499	32.3	4.4	130	DS125
				180	-	845	744	33.8	6.1	139	-	744	655	32.9	5.9	126	
				270	1x	1210	1065	35.0	9.5	128	0.49	1065	937	34.0	9.2	116	
				405	1.5x	1775	1562	36.4	14.8	120	-	1562	1375	35.5	14.4	109	
				540	2x	2274	2002	37.8	20.4	112	0.57	2001	1761	36.8	19.9	101	
Décor 10 Class A	BXRC-40A1001-C-73-SE	4000K	93	180	-	858	755	33.3	6.0	143	-	755	664	32.3	5.8	130	DS125
				240	-	1124	989	33.8	8.1	138	-	989	870	32.9	7.9	125	
				360	1x	1614	1420	35.0	12.6	128	0.37	1420	1250	34.0	12.3	116	
				540	1.5x	2350	2068	36.4	19.7	120	-	2068	1820	35.4	19.1	108	
				720	2x	3002	2641	37.7	27.1	111	0.43	2642	2324	36.7	26.4	100	
Décor 10 Class A	BXRC-40A1001-D-73-SE	4000K	93	175	-	628	553	24.9	4.4	144	-	553	486	24.2	4.2	130	DS125
				233	-	824	725	25.4	5.9	139	-	725	638	24.7	5.7	126	
				350	1x	1176	1035	26.0	9.1	129	0.49	1035	911	25.3	8.9	117	
				525	1.5x	1731	1523	27.4	14.4	120	-	1523	1341	26.7	14.0	109	
				700	2x	2218	1952	28.4	19.9	111	0.57	1952	1718	27.7	19.4	101	
Décor 13 Class A	BXRC-30A2001-B-73-SE	3000K	93	113	-	500	450	32.3	3.7	137	-	440	396	31.4	3.6	124	DS125
				225	-	968	871	33.2	7.5	130	-	852	766	32.3	7.3	117	
				450	1x	1836	1652	35.0	15.8	117	0.28	1616	1454	34.1	15.3	105	
				675	1.5x	2653	2387	36.3	24.5	108	-	2335	2101	35.4	23.9	98	
				900	2x	3384	3045	37.5	33.7	100	0.35	2978	2680	36.6	32.9	90	
Décor 13 Class A	BXRC-30A2001-C-73-SE	3000K	93	158	-	694	625	32.3	5.1	136	-	611	550	31.5	5.0	123	DS125
				315	-	1344	1210	33.2	10.5	128	-	1183	1065	32.4	10.2	116	
				630	1x	2570	2313	35.0	22.1	117	0.20	2262	2035	34.1	21.5	105	
				945	1.5x	3689	3320	36.4	34.4	107	-	3246	2921	35.6	33.6	97	
				1260	2x	4708	4237	37.8	47.6	99	0.24	4143	3729	36.9	46.5	89	
Décor 13 Class A	BXRC-30A2001-D-73-SE	3000K	93	125	-	495	446	29.6	3.7	134	-	435	392	28.7	3.6	122	DS125
				250	-	959	864	30.3	7.6	126	-	844	760	29.4	7.4	115	
				500	1x	1869	1683	31.8	15.9	118	0.34	1645	1481	30.9	15.5	106	
				750	1.5x	2641	2378	33.2	24.9	106	-	2324	2093	32.3	24.2	96	
				1000	2x	3377	3041	34.4	34.4	98	0.41	2972	2676	33.5	33.5	89	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T_c 25°C (lm)	Minimum Pulsed Flux T_c 25°C (lm)	Vf T_c 25°C (V)	Power T_c 25°C (W)	Typical Efficacy T_c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T_c 85°C (lm)	Minimum DC Flux T_c 85°C (lm)	Vf T_c 85°C (V)	Power T_c 85°C (W)	Typical Efficacy T_c 85°C (lm/W)	Data Sheet
Décor 13 Class A	BXRC-35A2001-B-73-SE	3500K	93	113	-	538	484	32.3	3.7	147	-	473	426	31.4	3.6	133	DS125
				225	-	1041	936	33.2	7.5	139	-	916	824	32.3	7.3	126	
				450	1x	1974	1776	35.0	15.8	125	0.28	1737	1563	34.1	15.3	113	
				675	1.5x	2853	2567	36.3	24.5	117	-	2510	2259	35.4	23.9	105	
Décor 13 Class A	BXRC-35A2001-C-73-SE	3500K	93	900	2x	3639	3274	37.5	33.7	108	0.35	3202	2881	36.6	32.9	97	DS125
				158	-	747	672	32.3	5.1	146	-	657	591	31.5	5.0	132	
				315	-	1445	1300	33.2	10.5	138	-	1272	1144	32.4	10.2	125	
				630	1x	2763	2486	35.0	22.1	125	0.20	2431	2188	34.1	21.5	113	
Décor 13 Class A	BXRC-35A2001-D-73-SE	3500K	93	945	1.5x	3966	3568	36.4	34.4	115	-	3490	3140	35.6	33.6	104	DS125
				1260	2x	5061	4554	37.8	47.6	106	0.24	4454	4008	36.9	46.5	96	
				125	-	532	479	29.6	3.7	144	-	468	421	28.7	3.6	131	
				250	-	1031	928	30.3	7.6	136	-	907	816	29.4	7.4	123	
Décor 13 Class A	BXRC-40A2001-B-73-SE	4000K	93	500	1x	2009	1808	31.8	15.9	126	0.34	1768	1591	30.9	15.5	114	DS125
				750	1.5x	2839	2555	33.2	24.9	114	-	2498	2248	32.3	24.2	103	
				1000	2x	3630	3267	34.4	34.4	105	0.41	3194	2875	33.5	33.5	95	
				113	-	2983	517	32.3	3.7	817	-	2625	455	31.4	3.6	739	
Décor 13 Class A	BXRC-40A2001-C-73-SE	4000K	93	225	-	3814	1002	33.2	7.5	510	-	3357	881	32.3	7.3	462	DS125
				450	1x	2111	1900	35.0	15.8	134	0.28	1858	1672	34.1	15.3	121	
				675	-	3051	2746	36.3	24.5	125	-	2685	2416	35.4	23.9	112	
				900	2x	3891	3502	37.5	33.7	115	0.35	3424	3082	36.6	32.9	104	
Décor 13 Class A	BXRC-40A2001-D-73-SE	4000K	93	158	-	798	719	32.3	5.1	156	-	703	632	31.5	5.0	141	DS125
				315	-	1546	1391	33.2	10.5	148	-	1360	1224	32.4	10.2	133	
				630	1x	2955	2660	35.0	22.1	134	0.20	2600	2341	34.1	21.5	121	
				945	-	4241	3818	36.4	34.4	123	-	3732	3360	35.6	33.6	111	
Décor 13 Class A	BXRC-40A2001-D-73-SE	4000K	93	1260	2x	5413	4873	37.8	47.6	114	0.24	4764	4288	36.9	46.5	102	DS125
				125	-	569	512	29.6	3.7	154	-	501	451	28.7	3.6	140	
				250	-	1103	993	30.3	7.6	145	-	971	874	29.4	7.4	132	
				500	1x	2150	1936	31.8	15.9	135	0.34	1892	1704	30.9	15.5	122	
Décor 18 Class A	BXRC-30A4001-B-73-SE	3000K	93	750	-	3038	2736	33.2	24.9	122	-	2674	2408	32.3	24.2	110	DS125
				1000	2x	3885	3498	34.4	34.4	113	0.41	3419	3078	33.5	33.5	102	
				450	-	1984	1786	33.3	15.0	132	-	1746	1572	32.4	14.6	120	
				600	-	2603	2343	33.9	20.4	128	-	2291	2062	33.1	19.8	116	
Décor 18 Class A	BXRC-30A4001-C-73-SE	3000K	93	900	1x	3696	3327	35.0	31.5	117	0.15	3252	2928	34.1	30.7	106	DS125
				1350	1.5x	5497	4948	36.7	49.5	111	-	4837	4354	35.8	48.3	100	
				1800	2x	7074	6368	38.0	68.4	103	0.19	6225	5603	37.1	66.8	93	
				585	-	2512	2260	33.4	19.5	129	-	2210	1989	32.6	19.1	116	
Décor 18 Class A	BXRC-30A4001-D-73-SE	3000K	93	780	-	3291	2962	34.0	26.5	124	-	2896	2606	33.3	25.9	112	DS125
				1170	1x	4807	4326	35.0	41.0	117	0.11	4230	3807	34.3	40.1	106	
				1755	1.5x	6915	6223	36.8	64.5	107	-	6086	5477	36.0	63.2	96	
				2340	2x	8870	7983	38.1	89.3	99	0.13	7806	7025	37.4	87.6	89	
Décor 18 Class A	BXRC-30A4001-D-73-SE	3000K	93	525	-	1915	1723	27.7	14.6	132	-	1685	1516	26.8	14.1	120	DS125
				700	-	2490	2240	28.2	19.8	126	-	2191	1971	27.3	19.1	115	
				1050	1x	3594	3234	29.0	30.5	118	0.16	3163	2846	28.1	29.5	107	
				1575	1.5x	5134	4619	30.4	47.9	107	-	4517	4065	29.5	46.5	97	
Décor 18 Class A	BXRC-35A4001-B-73-SE	3500K	93	2100	2x	6535	5880	31.5	66.2	99	0.19	5751	5175	30.6	64.3	89	DS125
				450	-	2134	1920	33.3	15.0	142	-	1878	1690	32.4	14.6	129	
				600	-	2799	2519	33.9	20.4	137	-	2463	2216	33.1	19.8	124	
				900	1x	3974	3576	35.0	31.5	126	0.15	3497	3147	34.1	30.7	114	
Décor 18 Class A	BXRC-35A4001-C-73-SE	3500K	93	1350	1.5x	5911	5319	36.7	49.5	119	-	5201	4680	35.8	48.3	108	DS125
				1800	2x	7606	6844	38.0	68.4	111	0.19	6693	6023	37.1	66.8	100	
				585	-	2700	2430	33.4	19.5	138	-	2376	2138	32.6	19.1	124	
				780	-	3538	3184	34.0	26.5	133	-	3113	2802	33.3	25.9	120	
Décor 18 Class A	BXRC-35A4001-D-73-SE	3500K	93	1170	1x	5167	4650	35.0	41.0	126	0.11	4547	4092	34.3	40.1	113	DS125
				1755	1.5x	7433	6689	36.8	64.5	115	-	6541	5887	36.0	63.2	103	
				2340	2x	9535	8581	38.1	89.3	107	0.13	8391	7551	37.4	87.6	96	
				525	-	2058	1852	27.7	14.6	141	-	1811	1630	26.8	14.1	129	
Décor 18 Class A	BXRC-35A2001-D-73-SE	3500K	93	700	-	2677	2409	28.2	19.8	135	-	2355	2119	27.3	19.1	123	DS125
				1050	1x	3864	3477	29.0	30.5	127	0.16	3400	3060	28.1	29.5	115	
				1575	1.5x	5519	4966	30.4	47.9	115	-	4857	4370	29.5	46.5	104	
				2100	2x	7026	6322	31.5	66.2	106	0.19	6183	5564	30.6	64.3	96	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Décor 18 Class A	BXRC-40A4001-B-73-SE	4000K	93	450	-	2282	2054	33.3	15.0	152	-	2008	1808	32.4	14.6	138	DS125
				600	-	2994	2695	33.9	20.4	147	-	2635	2371	33.1	19.8	133	
				900	1x	4251	3826	35.0	31.5	135	0.15	3741	3367	34.1	30.7	122	
				1350	1.5x	6323	5690	36.7	49.5	128	-	5564	5008	35.8	48.3	115	
				1800	2x	8136	7323	38.0	68.4	119	0.19	7160	6444	37.1	66.8	107	
Décor 18 Class A	BXRC-40A4001-C-73-SE	4000K	93	585	-	2888	2599	33.4	19.5	148	-	2541	2287	32.6	19.1	133	DS125
				780	-	3784	3406	34.0	26.5	143	-	3330	2997	33.3	25.9	128	
				1170	1x	5527	4974	35.0	41.0	135	0.11	4864	4377	34.3	40.1	121	
				1755	1.5x	7951	7156	36.8	64.5	123	-	6997	6297	36.0	63.2	111	
				2340	2x	10199	9179	38.1	89.3	114	0.13	8975	8077	37.4	87.6	103	
Décor 18 Class A	BXRC-40A4001-D-73-SE	4000K	93	525	-	2202	1982	27.7	14.6	151	-	1938	1744	26.8	14.1	138	DS125
				700	-	2864	2577	28.2	19.8	145	-	2520	2268	27.3	19.1	132	
				1050	1x	4134	3720	29.0	30.5	136	0.16	3638	3274	28.1	29.5	123	
				1575	1.5x	5905	5313	30.4	47.9	123	-	5196	4676	29.5	46.5	112	
				2100	2x	7517	6764	31.5	66.2	114	0.19	6615	5952	30.6	64.3	103	
Décor 29 Class A	BXRC-30A10K1-B-73-SE	3000K	93	900	-	5874	5286	49.6	44.7	131	-	5169	4652	48.3	43.5	119	DS125
				1200	-	7750	6975	50.5	60.6	128	-	6820	6138	49.1	59.0	116	
				1800	1x	11209	10088	52.0	93.6	120	0.06	9864	8877	50.7	91.2	108	
				2700	1.5x	16527	14874	54.1	146.1	113	-	14543	13089	52.8	142.5	102	
				3600	2x	21308	19177	55.8	201.0	106	0.07	18751	16876	54.5	196.3	96	
Décor 29 Class A	BXRC-30A10K1-C-73-SE	3000K	93	855	-	8065	7259	66.2	56.6	143	-	7097	6388	65.1	55.7	127	DS125
				1140	-	10250	9226	67.3	76.7	134	-	9020	8119	66.2	75.5	119	
				1710	1x	14197	12778	69.4	118.7	120	0.04	12493	11245	68.4	116.9	107	
				2565	1.5x	20140	18127	72.1	185.0	109	-	17723	15952	71.1	182.3	97	
				3420	2x	25244	22721	74.4	254.6	99	0.05	22215	19994	73.4	251.0	89	
Décor 29 Class A	BXRC-30A10K1-D-73-SE	3000K	93	1050	-	5195	4675	35.4	37.2	140	-	4571	4114	34.1	35.8	128	DS125
				1400	-	6685	6017	36.2	50.7	132	-	5883	5295	34.9	48.8	120	
				2100	1x	9444	8500	37.6	79.0	120	0.06	8311	7480	36.3	76.2	109	
				3150	1.5x	13445	12101	39.5	124.4	108	-	11832	10649	38.2	120.2	98	
				4200	2x	16945	15252	41.2	173.0	98	0.07	14912	13421	39.9	167.5	89	
Décor 29 Class A	BXRC-35A10K1-B-73-SE	3500K	93	900	-	6314	5683	49.6	44.7	141	-	5556	5001	48.3	43.5	128	DS125
				1200	-	8331	7498	50.5	60.6	138	-	7332	6598	49.1	59.0	124	
				1800	1x	12050	10845	52.0	93.6	129	0.06	10604	9544	50.7	91.2	116	
				2700	1.5x	17767	15990	54.1	146.1	122	-	15635	14071	52.8	142.5	110	
				3600	2x	22907	20616	55.8	201.0	114	0.07	20158	18142	54.5	196.3	103	
Décor 29 Class A	BXRC-35A10K1-C-73-SE	3500K	93	855	-	8670	7804	66.2	56.6	153	-	7630	6867	65.1	55.7	137	DS125
				1140	-	11020	9918	67.3	76.7	144	-	9698	8728	66.2	75.5	128	
				1710	1x	15263	13737	69.4	118.7	129	0.04	13431	12089	68.4	116.9	115	
				2565	1.5x	21652	19488	72.1	185.0	117	-	19054	17149	71.1	182.3	105	
				3420	2x	27139	24426	74.4	254.6	107	0.05	23883	21495	73.4	251.0	95	
Décor 29 Class A	BXRC-35A10K1-D-73-SE	3500K	93	1050	-	5585	5026	35.4	37.2	150	-	4914	4423	34.1	35.8	137	DS125
				1400	-	7187	6468	36.2	50.7	142	-	6325	5692	34.9	48.8	130	
				2100	1x	10153	9137	37.6	79.0	129	0.06	8935	8041	36.3	76.2	117	
				3150	1.5x	14454	13008	39.5	124.4	116	-	12720	11447	38.2	120.2	106	
				4200	2x	18218	16395	41.2	173.0	105	0.07	16031	14427	39.9	167.5	96	
Décor 29 Class A	BXRC-40A10K1-B-73-SE	4000K	93	900	-	6754	6079	49.6	44.7	151	-	5944	5349	48.3	43.5	137	DS125
				1200	-	8912	8021	50.5	60.6	147	-	7843	7058	49.1	59.0	133	
				1800	1x	12890	11601	52.0	93.6	138	0.06	11343	10209	50.7	91.2	124	
				2700	1.5x	19005	17105	54.1	146.1	130	-	16724	15052	52.8	142.5	117	
				3600	2x	24504	22054	55.8	201.0	122	0.07	21563	19407	54.5	196.3	110	
Décor 29 Class A	BXRC-40A10K1-C-73-SE	4000K	93	855	-	9275	8347	66.2	56.6	164	-	8162	7346	65.1	55.7	147	DS125
				1140	-	11788	10609	67.3	76.7	154	-	10374	9336	66.2	75.5	137	
				1710	1x	16327	14694	69.4	118.7	138	0.04	14368	12931	68.4	116.9	123	
				2565	1.5x	23162	20845	72.1	185.0	125	-	20382	18344	71.1	182.3	112	
				3420	2x	29031	26128	74.4	254.6	114	0.05	25547	22992	73.4	251.0	102	
Décor 29 Class A	BXRC-40A10K1-D-73-SE	4000K	93	1050	-	5974	5377	35.4	37.2	161	-	5257	4732	34.1	35.8	147	DS125
				1400	-	7689	6920	36.2	50.7	152	-	6766	6089	34.9	48.8	139	
				2100	1x	10861	9775	37.6	79.0	138	0.06	9558	8602	36.3	76.2	125	
				3150	1.5x	15462	13916	39.5	124.4	124	-	13607	12246	38.2	120.2	113	
				4200	2x	19488	17539	41.2	173.0	113	0.07	17149	15435	39.9	167.5	102	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Décor 10 Ultra	BXRC-27H1000-B-7x-SE	2700K	97 (typical)	135	-	548	482	33.3	4.5	122	-	493	434	32.3	4.4	113	DS124
				180	-	718	632	33.8	6.1	118	-	646	569	32.9	5.9	109	
				270	1x	1028	905	35.0	9.5	109	0.49	925	815	34.0	9.2	101	
				405	1.5x	1508	1328	36.4	14.8	102	-	1357	1195	35.5	14.4	94	
				540	2x	1932	1701	37.8	20.4	95	0.57	1739	1531	36.8	19.9	88	
Décor 10 Ultra	BXRC-27H1000-C-7x-SE	2700K	97 (typical)	180	-	729	641	33.3	6.0	122	-	656	577	32.3	5.8	113	DS124
				240	-	955	840	33.8	8.1	118	-	859	756	32.9	7.9	109	
				360	1x	1371	1206	35.0	12.6	109	0.37	1234	1085	34.0	12.3	101	
				540	1.5x	1996	1756	36.4	19.7	102	-	1797	1580	35.4	19.1	94	
				720	2x	2550	2243	37.7	27.1	94	0.43	2295	2019	36.7	26.4	87	
Décor 10 Ultra	BXRC-27H1000-D-7x-SE	2700K	97 (typical)	175	-	533	470	24.9	4.4	122	-	480	423	24.2	4.2	113	DS124
				233	-	700	616	25.4	5.9	118	-	630	555	24.7	5.7	110	
				350	1x	999	880	26.0	9.1	110	0.49	899	792	25.3	8.9	102	
				525	1.5x	1470	1295	27.4	14.4	102	-	1323	1166	26.7	14.0	95	
				700	2x	1884	1660	28.4	19.9	95	0.57	1696	1494	27.7	19.4	87	
Décor 10 Ultra	BXRC-30H1000-B-7x-SE	3000K	97 (typical)	135	-	587	516	33.3	4.5	131	-	528	465	32.3	4.4	121	DS124
				180	-	769	677	33.8	6.1	126	-	692	609	32.9	5.9	117	
				270	1x	1101	969	35.0	9.5	117	0.49	991	872	34.0	9.2	108	
				405	1.5x	1615	1422	36.4	14.8	109	-	1454	1279	35.5	14.4	101	
				540	2x	2069	1821	37.8	20.4	101	0.57	1862	1639	36.8	19.9	94	
Décor 10 Ultra	BXRC-30H1000-C-7x-SE	3000K	97 (typical)	180	-	780	687	33.3	6.0	130	-	702	618	32.3	5.8	121	DS124
				240	-	1023	900	33.8	8.1	126	-	920	810	32.9	7.9	117	
				360	1x	1468	1292	35.0	12.6	117	0.37	1321	1163	34.0	12.3	108	
				540	1.5x	2138	1881	36.4	19.7	109	-	1924	1693	35.4	19.1	101	
				720	2x	2731	2403	37.7	27.1	101	0.43	2458	2163	36.7	26.4	93	
Décor 10 Ultra	BXRC-30H1000-D-7x-SE	3000K	97 (typical)	175	-	571	503	24.9	4.4	131	-	514	453	24.2	4.2	121	DS124
				233	-	749	660	25.4	5.9	127	-	675	594	24.7	5.7	117	
				350	1x	1070	942	26.0	9.1	118	0.49	963	848	25.3	8.9	109	
				525	1.5x	1575	1387	27.4	14.4	110	-	1417	1248	26.7	14.0	101	
				700	2x	2018	1776	28.4	19.9	101	0.57	1816	1599	27.7	19.4	94	
Décor 13 Ultra	BXRC-27H2000-B-7x-SE	2700K	97 (typical)	113	-	487	439	32.3	3.7	133	-	438	395	31.4	3.6	123	DS124
				225	-	943	849	33.2	7.5	126	-	849	764	32.3	7.3	117	
				450	1x	1789	1611	35.0	15.8	114	0.49	1610	1450	34.1	15.3	105	
				675	1.5x	2585	2328	36.3	24.5	106	-	2327	2095	35.4	23.9	97	
				900	2x	3298	2970	37.5	33.7	98	0.57	2968	2673	36.6	32.9	90	
Décor 13 Ultra	BXRC-27H2000-C-7x-SE	2700K	97 (typical)	158	-	677	609	32.3	5.1	132	-	609	548	31.5	5.0	123	DS124
				315	-	1310	1179	33.2	10.5	125	-	1179	1062	32.4	10.2	116	
				630	1x	2505	2255	35.0	22.1	114	0.37	2255	2030	34.1	21.5	105	
				945	1.5x	3595	3237	36.4	34.4	104	-	3236	2913	35.6	33.6	96	
				1260	2x	4589	4131	37.8	47.6	96	0.43	4130	3718	36.9	46.5	89	
Décor 13 Ultra	BXRC-27H2000-D-7x-SE	2700K	97 (typical)	125	-	483	434	29.6	3.7	131	-	434	391	28.7	3.6	121	DS124
				250	-	935	842	30.3	7.6	123	-	842	758	29.4	7.4	114	
				500	1x	1823	1641	31.8	15.9	115	0.49	1641	1477	30.9	15.5	106	
				750	1.5x	2576	2319	33.2	24.9	103	-	2319	2087	32.3	24.2	96	
				1000	2x	3294	2965	34.4	34.4	96	0.57	2965	2669	33.5	33.5	88	
Décor 13 Ultra	BXRC-30H2000-B-7x-SE	3000K	97 (typical)	113	-	521	469	32.3	3.7	143	-	469	422	31.4	3.6	132	DS124
				225	-	1008	907	33.2	7.5	135	-	907	817	32.3	7.3	125	
				450	1x	1912	1721	35.0	15.8	121	0.28	1721	1549	34.1	15.3	112	
				675	1.5x	2763	2487	36.3	24.5	113	-	2487	2238	35.4	23.9	104	
				900	2x	3525	3172	37.5	33.7	104	0.35	3172	2855	36.6	32.9	96	
Décor 13 Ultra	BXRC-30H2000-C-7x-SE	3000K	97 (typical)	158	-	723	651	32.3	5.1	142	-	651	586	31.5	5.0	131	DS124
				315	-	1400	1260	33.2	10.5	134	-	1260	1134	32.4	10.2	124	
				630	1x	2676	2409	35.0	22.1	121	0.20	2408	2168	34.1	21.5	112	
				945	1.5x	3841	3458	36.4	34.4	112	-	3457	3112	35.6	33.6	103	
				1260	2x	4902	4413	37.8	47.6	103	0.24	4412	3972	36.9	46.5	95	
Décor 13 Ultra	BXRC-30H2000-D-7x-SE	3000K	97 (typical)	125	-	515	464	29.6	3.7	140	-	464	417	28.7	3.6	129	DS124
				250	-	999	899	30.3	7.6	132	-	899	809	29.4	7.4	122	
				500	1x	1947	1752	31.8	15.9	122	0.34	1752	1577	30.9	15.5	113	
				750	1.5x	2751	2476	33.2	24.9	111	-	2476	2228	32.3	24.2	102	
				1000	2x	3518	3166	34.4	34.4	102	0.41	3166	2849	33.5	33.5	94	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Décor 18 Ultra	BXRC-27H4000-B-7x-SE	2700K	97 (typical)	450	-	1936	1741	33.3	15.0	129	-	1742	1567	32.4	14.6	119	DS124
				600	-	2539	2284	33.9	20.4	125	-	2285	2056	33.1	19.8	115	
				900	1x	3605	3243	35.0	31.5	114	0.28	3245	2919	34.1	30.7	106	
				1350	1.5x	5362	4823	36.7	49.5	108	-	4826	4341	35.8	48.3	100	
				1800	2x	6900	6207	38.0	68.4	101	0.35	6210	5586	37.1	66.8	93	
Décor 18 Ultra	BXRC-27H4000-C-7x-SE	2700K	97 (typical)	585	-	2448	2203	33.4	19.5	125	-	2204	1983	32.6	19.1	115	DS124
				780	-	3208	2887	34.0	26.5	121	-	2888	2599	33.3	25.9	111	
				1170	1x	4686	4217	35.0	41.0	114	0.20	4217	3795	34.3	40.1	105	
				1755	1.5x	6741	6067	36.8	64.5	104	-	6067	5460	36.0	63.2	96	
				2340	2x	8647	7782	38.1	89.3	97	0.24	7782	7004	37.4	87.6	89	
Décor 18 Ultra	BXRC-27H4000-D-7x-SE	2700K	97 (typical)	525	-	1867	1680	27.7	14.6	128	-	1680	1512	26.8	14.1	119	DS124
				700	-	2427	2184	28.2	19.8	123	-	2184	1966	27.3	19.1	114	
				1050	1x	3504	3153	29.0	30.5	115	0.34	3154	2838	28.1	29.5	107	
				1575	1.5x	5005	4504	30.4	47.9	104	-	4504	4053	29.5	46.5	97	
				2100	2x	6371	5733	31.5	66.2	96	0.41	5734	5160	30.6	64.3	89	
Décor 18 Ultra	BXRC-30H4000-B-7x-SE	3000K	97 (typical)	450	-	2067	1860	33.3	15.0	138	-	1860	1674	32.4	14.6	127	DS124
				600	-	2712	2440	33.9	20.4	133	-	2440	2196	33.1	19.8	123	
				900	1x	3850	3465	35.0	31.5	122	0.28	3465	3119	34.1	30.7	113	
				1350	1.5x	5726	5153	36.7	49.5	116	-	5153	4638	35.8	48.3	107	
				1800	2x	7369	6632	38.0	68.4	108	0.35	6632	5968	37.1	66.8	99	
Décor 18 Ultra	BXRC-30H4000-C-7x-SE	3000K	97 (typical)	585	-	2616	2354	33.4	19.5	134	-	2354	2119	32.6	19.1	123	DS124
				780	-	3428	3085	34.0	26.5	129	-	3085	2777	33.3	25.9	119	
				1170	1x	5007	4506	35.0	41.0	122	0.20	4506	4055	34.3	40.1	112	
				1755	1.5x	7203	6482	36.8	64.5	112	-	6483	5834	36.0	63.2	103	
				2340	2x	9240	8315	38.1	89.3	104	0.24	8316	7484	37.4	87.6	95	
Décor 18 Ultra	BXRC-30H4000-D-7x-SE	3000K	97 (typical)	525	-	1994	1795	27.7	14.6	137	-	1795	1616	26.8	14.1	127	DS124
				700	-	2593	2334	28.2	19.8	131	-	2334	2101	27.3	19.1	122	
				1050	1x	3744	3370	29.0	30.5	123	0.34	3370	3033	28.1	29.5	114	
				1575	1.5x	5348	4814	30.4	47.9	112	-	4813	4332	29.5	46.5	103	
				2100	2x	6808	6128	31.5	66.2	103	0.41	6127	5515	30.6	64.3	95	
Décor 18 Food	BXRC-17E4000-B-74-SE	1700K	80	450	-	1422	1281	33.3	15.0	95	-	1280	1152	32.4	14.6	88	DS124
				600	-	1866	1680	33.9	20.4	92	-	1679	1512	33.1	19.8	85	
				900	1x	2649	2385	35.0	31.5	84	0.28	2384	2147	34.1	30.7	78	
				1350	1.5x	3940	3547	36.7	49.5	80	-	3546	3192	35.8	48.3	73	
				1800	2x	5070	4565	38.0	68.4	74	0.35	4563	4108	37.1	66.8	68	
Décor 18 Food	BXRC-17E4000-C-74-SE	1700K	80	585	-	1800	1620	33.4	19.5	92	-	1620	1458	32.6	19.1	85	DS124
				780	-	2359	2123	34.0	26.5	89	-	2123	1910	33.3	25.9	82	
				1170	1x	3445	3100	35.0	41.0	84	0.20	3101	2790	34.3	40.1	77	
				1755	1.5x	4956	4460	36.8	64.5	77	-	4460	4014	36.0	63.2	71	
				2340	2x	6357	5720	38.1	89.3	71	0.24	5721	5148	37.4	87.6	65	
Décor 18 Food	BXRC-17E4000-D-74-SE	1700K	80	525	-	1372	1235	27.7	14.6	94	-	1235	1111	26.8	14.1	88	DS124
				700	-	1784	1606	28.2	19.8	90	-	1606	1445	27.3	19.1	84	
				1050	1x	2576	2318	29.0	30.5	85	0.34	2318	2086	28.1	29.5	79	
				1575	1.5x	3679	3311	30.4	47.9	77	-	3312	2980	29.5	46.5	71	
				2100	2x	4684	4215	31.5	66.2	71	0.41	4216	3793	30.6	64.3	66	
Décor 18 Food	BXRC-25E4000-B-74-SE	2500K	80	450	-	2299	2069	33.3	15.0	153	-	2069	1862	32.4	14.6	142	DS124
				600	-	3016	2714	33.9	20.4	148	-	2714	2442	33.1	19.8	137	
				900	1x	4282	3853	35.0	31.5	136	0.28	3854	3468	34.1	30.7	126	
				1350	1.5x	6369	5731	36.7	49.5	129	-	5732	5158	35.8	48.3	119	
				1800	2x	8195	7374	38.0	68.4	120	0.35	7376	6637	37.1	66.8	110	
Décor 18 Food	BXRC-25E4000-C-74-SE	2500K	80	585	-	2909	2618	33.4	19.5	149	-	2618	2356	32.6	19.1	137	DS124
				780	-	3812	3431	34.0	26.5	144	-	3431	3088	33.3	25.9	132	
				1170	1x	5568	5011	35.0	41.0	136	0.20	5011	4510	34.3	40.1	125	
				1755	1.5x	8010	7209	36.8	64.5	124	-	7209	6488	36.0	63.2	114	
				2340	2x	10275	9247	38.1	89.3	115	0.24	9247	8322	37.4	87.6	106	
Décor 18 Food	BXRC-25E4000-D-74-SE	2500K	80	525	-	2218	1996	27.7	14.6	152	-	1996	1796	26.8	14.1	142	DS124
				700	-	2884	2596	28.2	19.8	146	-	2595	2336	27.3	19.1	136	
				1050	1x	4163	3747	29.0	30.5	137	0.34	3747	3372	28.1	29.5	127	
				1575	1.5x	5946	5352	30.4	47.9	124	-	5352	4817	29.5	46.5	115	
				2100	2x	7570	6813	31.5	66.2	114	0.41	6813	6132	30.6	64.3	106	

Form Factor	Part Number	CCT (Nominal)	CRI (min)	Current (mA)	Rated Current	Typical Pulsed Flux T _c 25°C (lm)	Minimum Pulsed Flux T _c 25°C (lm)	V _f T _c 25°C (V)	Power T _c 25°C (W)	Typical Efficacy T _c 25°C (lm/W)	Thermal Resistance Junction to Case ¹ (C/W)	Typical DC Flux T _c 85°C (lm)	Minimum DC Flux T _c 85°C (lm)	V _f T _c 85°C (V)	Power T _c 85°C (W)	Typical Efficacy T _c 85°C (lm/W)	Data Sheet
Décor 18 Specialty	BXRC-56G4001-B-74-SE	5600K	90	450	-	2448	2203	33.3	15.0	163	-	2203	1983	32.4	14.6	151	DS124
				600	-	3211	2890	33.9	20.4	158	-	2890	2601	33.1	19.8	146	
				900	1x	4559	4103	35.0	31.5	145	0.28	4103	3693	34.1	30.7	134	
				1350	1.5x	6781	6102	36.7	49.5	137	-	6103	5492	35.8	48.3	126	
				1800	2x	8725	7853	38.0	68.4	127	0.35	7853	7067	37.1	66.8	117	
Décor 18 Specialty	BXRC-56G4001-C-74-SE	5600K	90	585	-	3097	2787	33.4	19.5	159	-	2788	2509	32.6	19.1	146	DS124
				780	-	4059	3653	34.0	26.5	153	-	3653	3287	33.3	25.9	141	
				1170	1x	5928	5335	35.0	41.0	145	0.20	5335	4802	34.3	40.1	133	
				1755	1.5x	8528	7675	36.8	64.5	132	-	7675	6907	36.0	63.2	121	
				2340	2x	10939	9845	38.1	89.3	123	0.24	9845	8860	37.4	87.6	112	
Décor 18 Specialty	BXRC-56G4001-D-74-SE	5600K	90	525	-	2361	2125	27.7	14.6	162	-	2125	1912	26.8	14.1	151	DS124
				700	-	3071	2763	28.2	19.8	155	-	2764	2487	27.3	19.1	144	
				1050	1x	4433	3989	29.0	30.5	146	0.34	3990	3590	28.1	29.5	135	
				1575	1.5x	6332	5698	30.4	47.9	132	-	5699	5128	29.5	46.5	123	
				2100	2x	8061	7253	31.5	66.2	122	0.41	7254	6528	30.6	64.3	113	
Décor 29 Food	BXRC-17E10K0-B-74-SE	1700K	80	900	-	4209	3789	49.6	44.7	94	-	3788	3410	48.3	43.5	87	DS124
				1200	-	5554	4999	50.5	60.6	92	-	4999	4499	49.1	59.0	85	
				1800	1x	8033	7230	52.0	93.6	86	0.06	7230	6507	50.7	91.2	79	
				2700	1.5x	11844	10660	54.1	146.1	81	-	10659	9594	52.8	142.5	75	
				3600	2x	15271	13744	55.8	201.0	76	0.07	13744	12370	54.5	196.3	70	
Décor 29 Food	BXRC-17E10K0-C-74-SE	1700K	80	855	-	5780	5202	66.2	56.6	102	-	5202	4682	65.1	55.7	93	DS124
				1140	-	7346	6611	67.3	76.7	96	-	6612	5950	66.2	75.5	88	
				1710	1x	10175	9157	69.4	118.7	86	0.04	9158	8241	68.4	116.9	78	
				2565	1.5x	14434	12990	72.1	185.0	78	-	12991	11691	71.1	182.3	71	
				3420	2x	18092	16282	74.4	254.6	71	0.05	16283	14654	73.4	251.0	65	
Décor 29 Food	BXRC-17E10K0-D-74-SE	1700K	80	1050	-	3723	3351	35.4	37.2	100	-	3350	3016	34.1	35.8	94	DS124
				1400	-	4791	4313	36.2	50.7	95	-	4312	3881	34.9	48.8	88	
				2100	1x	6768	6092	37.6	79.0	86	0.06	6091	5483	36.3	76.2	80	
				3150	1.5x	9635	8673	39.5	124.4	77	-	8672	7806	38.2	120.2	72	
				4200	2x	12144	10931	41.2	173.0	70	0.07	10929	9838	39.9	167.5	65	
Décor 29 Food	BXRC-25E10K0-B-74-SE	2500K	80	900	-	6803	6123	49.6	44.7	152	-	6123	5511	48.3	43.5	141	DS124
				1200	-	8976	8079	50.5	60.6	148	-	8079	7271	49.1	59.0	137	
				1800	1x	12983	11685	52.0	93.6	139	0.06	11685	10517	50.7	91.2	128	
				2700	1.5x	19142	17228	54.1	146.1	131	-	17228	15506	52.8	142.5	121	
				3600	2x	24681	22213	55.8	201.0	123	0.07	22213	19992	54.5	196.3	113	
Décor 29 Food	BXRC-25E10K0-C-74-SE	2500K	80	855	-	9342	8408	66.2	56.6	165	-	8408	7567	65.1	55.7	151	DS124
				1140	-	11874	10686	67.3	76.7	155	-	10687	9618	66.2	75.5	142	
				1710	1x	16446	14801	69.4	118.7	139	0.04	14801	13321	68.4	116.9	127	
				2565	1.5x	23331	20997	72.1	185.0	126	-	20998	18897	71.1	182.3	115	
				3420	2x	29243	26318	74.4	254.6	115	0.05	26318	23686	73.4	251.0	105	
Décor 29 Food	BXRC-25E10K0-D-74-SE	2500K	80	1050	-	6018	5415	35.4	37.2	162	-	5416	4874	34.1	35.8	151	DS124
				1400	-	7744	6969	36.2	50.7	153	-	6970	6272	34.9	48.8	143	
				2100	1x	10940	9845	37.6	79.0	139	0.06	9846	8861	36.3	76.2	129	
				3150	1.5x	15575	14016	39.5	124.4	125	-	14017	12614	38.2	120.2	117	
				4200	2x	19630	17665	41.2	173.0	113	0.07	17667	15898	39.9	167.5	105	
Décor 29 Specialty	BXRC-56G10K1-B-74-SE	5600K	90	900	-	7244	6520	49.6	44.7	162	-	6519	5868	48.3	43.5	150	DS124
				1200	-	9558	8602	50.5	60.6	158	-	8602	7742	49.1	59.0	146	
				1800	1x	13824	12442	52.0	93.6	148	0.06	12442	11198	50.7	91.2	136	
				2700	1.5x	20382	18344	54.1	146.1	140	-	18344	16510	52.8	142.5	129	
				3600	2x	26279	23652	55.8	201.0	131	0.07	23651	21287	54.5	196.3	121	
Décor 29 Specialty	BXRC-56G10K1-C-74-SE	5600K	90	855	-	9947	8953	66.2	56.6	176	-	8952	8057	65.1	55.7	161	DS124
				1140	-	12642	11379	67.3	76.7	165	-	11378	10241	66.2	75.5	151	
				1710	1x	17510	15760	69.4	118.7	148	0.04	15759	14184	68.4	116.9	135	
				2565	1.5x	24840	22358	72.1	185.0	134	-	22356	20122	71.1	182.3	123	
				3420	2x	31135	28023	74.4	254.6	122	0.05	28021	25221	73.4	251.0	112	
Décor 29 Specialty	BXRC-56G10K1-D-74-SE	5600K	90	1050	-	6407	5766	35.4	37.2	172	-	5766	5190	34.1	35.8	161	DS124
				1400	-	8246	7421	36.2	50.7	163	-	7421	6679	34.9	48.8	152	
				2100	1x	11648	10483	37.6	79.0	148	0.06	10483	9435	36.3	76.2	138	
				3150	1.5x	16583	14924	39.5	124.4	133	-	14924	13432	38.2	120.2	124	
				4200	2x	20900	18810	41.2	173.0	121	0.07	18810	16929	39.9	167.5	112	