



SPECIFICATION:  
 PITCH BETWEEN POLES:2.0mm  
 CURRENT RATING:2A  
 VOLTAGE RATING:250V  
 CONTACT RESISTANCE:INITIAL VALUE/10mΩ max.  
 AFTER ENVIRONMENTAL TESTING/20mΩ max.  
 INSULATION RESISTANCE:1000MΩ (min.)  
 WITHSTAND VOLTAGE:800V AC/MINUTE  
 TEMPERATURE RANGE:-25°C TO+85°C  
 APPLICABLE WIRE:AWG#24TO#30  
 FEATURES:  
 AVAILABLE NUMBER OF CIRCUITS 2 TO 16  
 MATERIAL:NYLON 66 UL94V-0  
 ACCEPTS:2004-T CRIMP TERMINAL

Dimension & Ordering Information

Poles	DIM(mm)	
	A	B
2	2.0	5.2
3	4.0	7.2
4	6.0	9.2
5	8.0	11.2
6	10.0	13.2
7	12.0	15.2
8	14.0	17.2
9	16.0	19.2
10	18.0	21.2
11	20.0	23.2
12	22.0	25.2
13	24.0	27.2
14	26.0	29.2
15	28.0	31.2
16	30.0	33.2

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Angel	 TOLERANCE: .000:±0.08 .00:±0.13 .0:±0.25 SCALE 比例 參考 UNIT 單位 M M SIZE 紙張尺寸 A 4 PAGE 張數 1 OF 1 REV. 版次 A	PART NAME 品名 2.0mm HOUSING 1XXXP WHITE COLOR LOW-LEAD	
DWG. 製圖 Yumi		PART NO. 料號 H2007-XXPW0000R	
DATE 制表日 2010/10/25			