



PCB LAYOUT

NOTE:

1. Shielded – 0.25mm THICKNESS BRASS C2680 H. PLATING NICKEL 20u” Min.
2. Housing – Standard Material LCP, Glass Filled Polyester UL94V-0 Standard Color Black.
3. RJ Terminal – Plastic: LCP UL94V-0, Standard Color Black. Pin: 0.35mm Thickness Phos-Bronze C5210 EH. Plating: Nickel 40u”~60u” for all and Sn 100% ,and Gold Plating.
4. Input Terminal – Plastic: LCP, Glass Filled, UL94V-0, Standard Color Black. Pin: 0.35mm SUS430. Plating: Nickel 40u”~60u” for all and Sn 100%.

**Industrial operation temp.: -40 degree C ~ + 85 degree C

| | | | |
|---------------------|----------------|--|--|
| RoHS Compliant | | HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD. | |
| APPD. 核准 | SCALE 比例 参考 | TOLERANCE UNLESS OTHERWISE SPECIFIED .X± 0.38 X'± 2.0' .XX± 0.20 .X'± 1.0' .XXX± 0.10 | PART NAME 品名 RJ45 TRANSFORMER PCB JACK 10/100/1000 UP LATCH W/ SHIELDED(BEHIND PEG 3.05mm) W/ TABS FLAT PIN W/ BI-COLOR LED LIGHT (GREEN & YELLOW) TRANSFORMER TYPE: TYPE 1 OPERATION TEMP.: -40°C ~ +85°C BLACK COLOR ROHS |
| DWG. 製圖 Betty | UNIT 單位 MM | SIZE. 紙張尺寸 A4 | PART NO. |
| DATE 制表日 2022/09/07 | PAGE 張數 1 OF 2 | REV. 版次 A | 料號 C0241-88YXB411R |

