



Pc Board Layout

**SPECIFICATION**

Current Rating: 1Amp  
 Insulator Resistance: 5000 Megohms Min.  
 Contact Resistance: 20 Milliohms Max.  
 Dielectric Withstanding: AC 500V  
 Operating Temperature: -40°C ~ +105°C  
 Max Processing Temp: 230°C For 60 Seconds  
 260°C For 10 Seconds  
 Insulator Material: Polysphor, UL 94V-0  
 Standard: Nylon-6T  
 Contact Material: Phosphor Bronze.  
 Finish: Gold Flash All Over

Pins	A	B	Pins	A	B
2x01	2.0	---	2x21	42.0	40.0
2x02	4.0	2.0	2x22	44.0	42.0
2x03	6.0	4.0	2x23	46.0	44.0
2x04	8.0	6.0	2x24	48.0	46.0
2x05	10.0	8.0	2x25	50.0	48.0
2x06	12.0	10.0	2x26	52.0	50.0
2x07	14.0	12.0	2x27	54.0	52.0
2x08	16.0	14.0	2x28	56.0	54.0
2x09	18.0	16.0	2x29	58.0	56.0
2x10	20.0	18.0	2x30	60.0	58.0
2x11	22.0	20.0	2x31	62.0	60.0
2x12	24.0	22.0	2x32	64.0	62.0
2x13	26.0	24.0	2x33	66.0	64.0
2x14	28.0	26.0	2x34	68.0	66.0
2x15	30.0	28.0	2x35	70.0	68.0
2x16	32.0	30.0	2x36	72.0	70.0
2x17	34.0	32.0	2x37	74.0	72.0
2x18	36.0	34.0	2x38	76.0	74.0
2x19	38.0	36.0	2x39	78.0	76.0
2x20	40.0	38.0	2x40	80.0	78.0

APPD. 核准 BETTY DWG. 製圖 KAREN DATE 制表日 2012/04/20		<b>玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	PART NAME 品名 2.0mm FEMALE HEADER DUAL ROW H:4.3mm W:4.0mm 2*XXP 180° BLACK INSULATOR ROHS
			PART NO. 料號 C6801-XXBSXL00R
TOLERANCE 容許公差 0 ± .00 ± ANG ±	SCALE 比例 參考	UNIT 單位 MM	SIZE 紙張尺寸 A4
PAGE 張數 1 OF 1	REV. 版本 B		