





PIN ASSIGNMENT



NOTE: SAS线地线就近接地;
HD的3/6/9及SATA的1/7pin为GND, 所有GND均导通

XXXXXXXXXXXXX L285HM017-SD-R REV X1 DD/MMM/YY	XXXXXXXXXXXXX L285HM017-SD-R REV X1 DD/MMM/YY
--	--

PRINT DETAIL(打印要求):
1.FONTS(字体):Arial;
2.HEIGHT(字高): 2mm;
3.COLOR: WHITE(白底黑字);
4.DD/MMM/YY(日/月/年)
EXAMPLE: 31/DEC/2018

NOTE(说明):
1.ALL CABLE 100% OPEN, SHORT, MISS WIRE& TRANSIENT FAULT TEST;
(所有产品必须100%进行断路、短路、错位及间隙性接触测试)
2.THE DIMENSIONS MARKED ▼ SHALL BE CHECKED;
(标注 ▼ 的尺寸必须重点检验)
3.CONDUCTOR RESISTANCE(导通阻抗):1.0 ohm Max;
4.INSULATION RESISTANCE(绝缘阻抗):20 ohm Min/300VDC@10ms;
5.CONTACT RESISTANCE(接触阻抗):1.0 ohm Max
6.HIGH FREQUENCY CHARACTERISTIC PLEASE FOLLOW SAS 3.0 STANDARD.
(高频特性:符合 SAS 3.0 规范要求),
7.Connector Impedance: 100±15% ohm, Cable Impedance: 100±10% ohm
(连接器阻抗: 100±15% ohm, 线材阻抗: 100±10% ohm)
8.ALL MATERIALS AND PROCESS MUST BE MEET THE REQUIREMENT OF QW-Q-043.
(本产品使用物料及制程须符合:QW-Q-043文件对应环境物质管理要求.)
9.THE DIMENSIONS OF MOLDING MUST BE MEET THE REQUIREMENT OF 1932007839.
(内部产品模型重点尺寸管控标准请参考文件1932007839.)
10.PROCESS MUST BE MEET THE REQUIREMENT OF 1972000010.
制程加工要求必须符合: 产品制程工艺规范(文档号1972000010)要求。

X.± 1	X.°± /	Customer P/N:	LUXSHARE-TECH		
.X± 0.3	.X°± /	Customer REV.:			
.XX± 0.20	.XX°± /	PART NO. L285HM017-SD-R	TITLE: HD MINI SAS TO 4x SATA 7P/F 180°+ 2*4P H.S CABLE		
.XXX± 0.100	.XXX°± /	APPROVED: ZHENG ZENG	DWG NO: RDS2308028-025		
UNITS:	mm	CHECKED: DONG SHEN		SCALE	SHEET
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF LUXSHARE-TECH AND SHALL NOT BE REPRODUCED, COPIED OR CUED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF LUXSHARE-TECH		DRAWN: DARA PENG		NONE	2/2
					REV. X1