

REV	CONTENT	CHK	DATE
V0.0	CONTENT	ZCL	24.11.08

Electrical :

- UL IEC
- 1.Rated Voltage : 300V 500V
- 2.Rated Current : 16A 20A
- 3.Withstanding Voltage : AC1600V/1Min.
- 4.Operating Temperature : -40°C~+130°C
- 5.RoHS Compliance
- 6."★" is the key quality control point

9EGTVC - 7.5 -06P - X X - 00

① ② ③ ④ ⑤ ⑥

- ① Series NO. ④ 1 Single Pitch
2 Double Pitch






- ② Pitch ⑤ Color: 1 Grey
2 Blue
3 Black
4 Green
5 Orange
6 Red
7 Transparent
8 Yellow
9 White

- ⑥ Customer Request: 00--Standard

2	PIN	XX	6	Copper	Au Plated
1	HOUSING	XX	1	PA66+GF UL94V-0	SEE NOTE
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	ZCL	DATE	24.11.08	SIZE	A4 UNITS mm SHEET/OF 1/1
CHK.	DATE		SCALE	1:1	
APP.	DATE		NAME	9EGTVC-7.5-06P-XX-00	
			DWGNO.	XXXX	

Grolten

宁波冠泰电子有限公司
NINGBO GOLTEN ELECTRONICS CO., LTD.



A	Total Pitch Tolerances									Nominal dimension range									$\perp$		$\equiv$		—		$//$	
	in mm									in mm																
	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 250	over 350	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 0	over 10	all	over 0	over 100	over 150		
	to 30	to 53	to 70	to 90	to 115	to 150	to 250	to 350	to 500	to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 320	to 10	to 10		to 100	to 150	to 150		
	± 0.18	± 0.20	± 0.25	± 0.3	± 0.35	± 0.44	± 0.60	± 0.70	± 0.85	± 0.20	± 0.25	± 0.30	± 0.35	± 0.44	± 0.55	± 0.70	± 0.80	± 0.90	0.2	0.3	0.3	0.2	0.3	0.5		