



1. APPLICATION AND FEATURES

- * Compact and low profile design for saving space.
- * High reliable contact with low insertion force.
- * Straight and right angle type facilitate engineering design.
- * Mate with flexible Printed Circuit.

2. SPECIFICATIONS

- * Current Rating : 3 Amp
- * Insulator resistance : 5000 Megohms min. / 500v DC for 1 minutes.
- * Contact resistance : 20m ohm Max.
- * Dielectric withstanding : AC 500v for 1 minutes.
- * Operating Temperature : -40°C ~ 105°C
- * Contact Material : Phosphor Bronze
- * Insulator Material : Polyester, UL 94V-0, Standard P.B.T

"Solder temp. in oven is max. 180 degree C for 3 sec."

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY		GENERAL TOLERANCE 0.05/0.10/0.20/0.30/0.50/1.00/2.00/3.00/5.00/10.00/20.00/30.00/50.00/100.00/200.00/500.00/1000.00	PART NAME 品名 2.54mm FEMALE HEADER H:8.4mm GOLD FLASH ROHS
DWG. 製圖 BETTY	SCALE 比例 1:1	UNIT 單位 MM	SIZE 規格尺寸 A 4
DATE 制表日 2011/08/22	PAGE 張數 1 OF 1	REV. 版本 A	PART NO. 料號 C2806-XXXXGH00R