


TOL	± mm
A	1.5
B	3.0
C	4.6
D	25.0
E	5.0

NOTE :-

- 1) ALL DIMENSIONS ARE IN m.m.
- 2) DIMENSIONS INDICATED ARE APPROXIMATE AND THE SAME ARE SUBJECT TO CHANGE DUE TO DESIGN IMPROVEMENTS WITHOUT AFFECTING THE FUNCTIONAL PARAMETERS.
- 3) STAINLESS STEEL SHEET (409) THICKNESS - 1.5 mm.
- 4) CREEPAGE DISTANCE OF CAP. BUSHING - 380 mm.
- 5) INSULATION LEVEL - 38 / 95 KV.
- 6) COLOR SHADE - GRAY ANSI-70.
- 7) TERMINAL CONNECTORS ARE NOT IN OUR SCOPE.
- 8) CASE SWELLING - 14 mm.

SUPPLIER		Shreem ELECTRIC LIMITED	
OWNER		ATOMA LTD, RUSSIA.	
CONTRACTOR			
PROJECT			
PO NO		PD-02, DTD. 23.12.2022	
SIGN	DATE	450 KVAR 6.3 KV, 3 Ø, 50 Hz, INTERNAL STAR INTERNAL FUSE CAPACITOR UNIT.	SCALE N. T. S.
DRAWN	17.11.22		SHEET NO. 1 OF 1
CHEKD	17.11.22		
APPRD	17.11.22		
DRG. NO. SR - QUH - A4 - 0574 - 01 - 2023			REV. 0
RELEASED FOR ☐ PRELIMINARY ☐ TENDER ☐ INFORMATION ☒ APPROVAL ☐ CONSTRUCTION			

